

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9652-3

-----  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 11, 12, 13, & 14, with brass cap mkd

T26S R2E  
S11|S12  
S14|S13  
1930

from which

- A fir, 36" dia., bears N.30°E., 18 lks., mkd: T26S R2E S12  
BT.
- A fir, 36" dia., bears S.46°E., 35 lks., mkd: T26S R2E S13  
BT.
- A fir, 28" dia., bears S.55°W., 64 lks., mkd: T26S R2E S14  
BT.
- A fir, 18" dia., bears N.77°W., 29 lks., mkd: T26S R2E S11  
BT.