

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Witness Cor. Secs. 1, 2, 11, & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9655 & 9657-8

Page 9655

Point for cor. of secs. 1, 2, 11, & 12, falls on steep insecure ground, impracticable to set cor.,
At point, 33 lks. N.0°16'W., set witness cor.

Page 9657-8

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for witness cor. to the cor. of secs. 1, 2, 11, & 12, with brass cap mkd

T26S R2E
S 2 | S 1
S11 | S12
W | C
1930

from which

- A fir, 12" dia., bears N.40°E., 59 lks., mkd: WC T26S R2E S1 BT.
- A hemlock, 20" dia., bears S.9°E., 75 lks., mkd: WC T26S R2E S12 BT.
- A hemlock, 10" dia., bears S.31°W., 83 lks., mkd: WC T26S R2E S11 BT.
- A fir, 14" dia., bears N.6°W., 61 lks., mkd: WC T26S R2E S2 BT.