

TOWNSHIP 25½ RANGE 02E POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Tps Cor

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9634

-----  
Set an iron post, 3 ft. long, 3" dia., 27" in the ground, for cor. of Tps. 25½ & 26 S, Rs. 2 & 3 E, with brass cap mkd.

T25½S  
R2E R3E  
S36 S31  
S 1 S 6  
T26S  
1930

from which

- A fir, 8" dia., bears N.69°E., 31 lks., mkd: T25½S R3E S31  
BT.
- A fir, 6" dia., bears S.51°E., 7 lks., mkd: T26S R3E S6  
BT.
- A fir, 6" dia., bears S.64°W., 41 lks., mkd: T26S R2E S1  
BT.
- A fir, 8" dia., bears N.31°W., 45 lks., mkd: T25½S R2E S36  
BT.