

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Cor. Secs. 12, 13; 7 & 18 T26-3E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9631-2

Set an iron post, 3 ft. long, 2" dia., 27" in the ground, for cor. of secs. 7, 12, 13, & 18, with brass cap mkd

T26S
R2E | R3E
S12 | S7
S13 | S18
1929

from which

- SW Cor. of Pine Bench shelter bears N.17°E., 251 lks.
- A pine, 32" dia., bears N.23°E., 23 lks., mkd: T26S R3E S7 BT.
- A cedar, 48" dia., bears S.44°E., 279 lks., mkd: T26S R3E S18 BT.
- A pine, 34" dia., bears S.53°W., 59 lks., mkd: T26S R2E S13 BT.
- A pine, 18" dia., bears N.7°W., 43 lks., mkd: T26S R2E S12 BT.