

PRIMARY CORNER DESCRIPTION Cor. No. 1 HES 227

Alias	Description
Alias	Description
Alias	Description
Alias	Description

HES No. 227 by Geo. W. Root, Forest Service Surveyor, under special instructions dated March 14, 1917 - Surveyed Oct. 1917 - DCSO records Vol. 28 Page(s) 12178)

 Cor. No. 1 of this survey, identical with cor. No. 1 of the listing survey, which is on line between cors. 1 & 2 of HES No. 142 as shown under "retracement" I destroy the listing cor. and in its place establish cor. No. 1 of this survey as follows:

- Set a granite stone, 24x10x8", 14" in the ground, over a stone marked with a cross for cor. No. 1 of this survey, marked 1 HES 227 on side facing the claim, from which
 - A fir, 50" dia., bears S.5°00'E., 42 lks., marked X 1 HES 227 BT.
 - A fir, 24" dia., bears N.57°00'E., 102 lks. marked X 1 HES 227 BT.
- Raise a mound of earth 4 ft. base, 2 ft. high, 3½ ft. within the claim.
- USLM No. 142, described in field notes of HES No. 93, bears S.0°35'W., 9.80 chs.
- Cor. No. 1 of HES No. 142, heretofore described, bears S.6°37'W., 4.63 chs.

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9723

 Cor. No. 1 HES No. 227, which is a fir, 34" dia., marked & witnessed as described in the official record.

Marvin C. Ramsey - For: J.H. Baxter & Co. - Witnesses: J. Goodin & R. Schultz - Sept. 12-22, 1960 - C.S. File 51/126

- Found - D.Fir sawed stump 50" bears S.5°E., 42 lks. with bottom part of axe face. Orig. BT
- D.Fir sawed stump 26" bears N.57°E., 102 lks., with bottom part of axe face. Orig. BT
- Set an IP 3' long 1½" dia. 28" in gr. mkd: RS404 from which
 - 18" D.Fir bears N.37°E., 47 lks. mkd: 1 HES 227 RS404 BT.
 - 16" D.Fir bears N.67°W., 59 lks. mkd: 1 HES 227 RS404 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - 10/27/1969 - C.S. File 52/43-13

 Found - 1½" I.P. at cor. point in good cond. & BTs called for in 1960 renewal as follows: cont. next pg

PRIMARY CORNER DESCRIPTION Cor. No. 1 HES 227

Alias	Description
Alias	Description
Alias	Description
Alias	Description

18" D.Fir N.37°E., 31.0 ft. alive - face burned - scribe visible.
16" D.Fir N.67°W., 38.9 ft. now - sawed stump - scribe visible.
New BT - 18" D.Fir N.56°W., 28.1 ft. mkd: 1 HES 227 CS BT"
Note - This cor. lies at fence cor. 40 ft. west of Gateway.
Remains of OBT stumps still evident.

Robert Dean, LS 1808 - For: USFS - Dec. 20, 1984 - M98-6 & C.S. File 58/204-11

This is a closing corner. At the intersection of lines 1-4 HES 227 with 1-2 HES 142 I set a 2"x30" magnetic aluminum monument marked "T26S R2E HES 142 HES 227 CC LS 1808 1984", in 36" cairn, from which

- A 1¼" galv. iron pipe with ¾" brass disc stamped "RS 404", per C.S. 51/126, bears S.50°10'W., 0.64', I stamped "AM" on the rim of this pipe, for "amended monument" found off line;
- A 40" burnt stump bears S.4°15'E., 28.3' (rec. S.5°E., 27.72' per HES 227)
- A 28" D.Fir stump, portion of face visible, 10" center, bears N.55°10'E. 68.5' (rec N.57°E. 67.32' per HES 227)
- A 16" D.Fir stump, "1HES227 RS 404 BT" visible, bears N.68°00'W., 38.9' (rec. N.67°W., 38.94' per 1960 ren.)
- A 21" D.Fir, healed scar, bears N.59°20'W., 28.4' (rec. N.56°W., 28.10' per 1969 ren.)
- A 24" D.Fir, healed scar, bears N.36°45'E., 30.8' (rec. N.37°E., 31.2' per 1960 ren.)