

PRIMARY CORNER DESCRIPTION Cor. No. 2 HES 229

Alias	Description
Alias	Description
Alias	Description
Alias	Description

HES No. 229 by Geo. W. Root, Forest Service Surveyor, under special instructions dated March 17, 1917 - Surveyed Oct. 1917 - DCSO records Vol. 28 Page(s) 12182)

To cor. No. 3 of the listing survey, which I destroy and in its place establish cor. No. 2 of this survey as follows:
Set a diorite stone, 24x8x6", 14" in the ground, over a stone marked with a cross for cor. No. 2 of this survey, marked 2 HES 229 on side facing the claim, from which

- A fir, 16" dia., bears N.82°00'E., 32 lks., marked X 2 HES 229 BT.
- A fir, 16" dia., bears N.28°00'E., 66 lks., marked X 2 HES 229 BT.

Dig pits, 24x24x12", crosswise on this and the succeeding course, 7 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist., within the claim.

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9721-2

Cor. No. 2 HES No. 229, which is a stone, 8x8x6" above ground, mkd & witnessed as described in the official record.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 10/31/1969 - C.S. File 52/43-27

Found - Corner stone, in place, mkd: "X" on top & "2 HES 229" on side facing claim.
Orig. 16", now 23" Fir, alive, N.82°E., 21.1 ft., shows good scar, we tag.
Orig. 16", now 22" Fir, Alive, N.28°E., 43.6 ft., shows good scar, we tag.

At corner point in place of old cor. stone:
Set - 1" IP & brass cap mkd. "COUNTY SURVEYORS OFFICE 1969 T26S COR. #2 HES --\ 229 R2E" & reset stone alongside.

New BT - 10" D.Fir, S.63°W., 24.6 ft. mkd: "2 HES 229 CS BT"
This corner lies on the edge of bench beginning to roll off to very steep NE slope.

Robert Dean - For: USFS - Dec. 1984 - M98-16 & C.S. 63/5-1

Found - 1" galvanized iron pipe, per 1969 ren with 2½" brass cap, (properly) mkd (a stone lies alongside), from which
A 27" D.Fir, healed scar, bears N.28°05'E., 41.8' (rec. N.28°E., 43.56' per HES 229) cont. next pg

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 929020

PRIMARY CORNER DESCRIPTION Cor. No. 2 HES 229

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 26" D.Fir, healed scar, bears N.86°40'E., 21.0'
(rec. N.82°E., 21.12' per HES 229)
A 12" D.Fir, healed scar, bears S.61°40'W., 24.4'
(rec. S.63°W., 24.6' per 1969 ren)