

PRIMARY CORNER DESCRIPTION Cor. No. 3 HES 229

Alias	Description
Alias	Description
Alias	Description
Alias	Description

HES No. 229 by Geo. W. Root, Forest Service Surveyor, under special instructions dated March 17, 1917 - Surveyed Oct. 1917 - DCSO records Vol. 28 Page(s) 12182-3)

Cor. No. 2 of listing survey, 20 ft. above trail, which I now destroy and in its place establish cor. No. 3 of this survey as follows:
Set a diorite stone, 24x12x10", 14" in the ground, over a stone marked with a cross for cor. No. 3 of this survey, marked 3 HES 229 on side facing the claim; from which
 A fir, 14" dia., bears S.56°16'E., 19 lks., marked X 3 HES 229 BT.
 A fir, 8" dia., bears N.26°45'E., 23 lks., marked X 3 HES 229 BT.
 Dig pits, 24x24x12", crosswise on this and the succeeding course, 7 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist., within the claim.

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9722

Cor. No. 3 HES No. 229, which is a stone, 12x10x10" above ground, mkd & witnessed as described in the official record.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 10/31/1969 - C.S. File 52/43-28

Found - Corner stone, in place, mkd: "X" HES 229"
 Orig. 14", now 22" Fir, alive, S.56¼°E., 12.5 ft., shows good scar, we tag.
 Orig. 8", now 15" Fir, alive, N.26°45'E., 15.2 ft. shows good scar. Rescribe: "3 HES 229 CS BT"
At cor. point
Set - 1" IP & brass cap mkd. "COUNTY SURVEYORS OFFICE 1969 T26S COR. #3 HES > 229 R2E" - reset old cor. stone along side.
New BT - 9" D.Fir S.81°W., 6.6 ft. mkd: "3 HES 229 CS BT"
This cor. lies on steep easterly slope that descents to Copeland Creek.

Robert Dean - For: USFS - Dec. 1984 - M98-16 & C.S. 63/5-1

Found - 1" galvanized iron pipe, per 1969 ren with 2½" brass cap, (properly) mkd (a stone lies alongside), from which
 A 14" D.Fir, healed scar, bears N.25°45'E., 15.0' (record N.26°45'E., 15.18 per HES 229) Continued

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 929030

PRIMARY CORNER DESCRIPTION Cor. No. 3 HES 229

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A 26" D.Fir, healed scar, bears S.54°40'E., 12.4'
(rec. S.56°15'E., 12.54' per HES 229)
An 11" D.Fir, healed scar, bears S.82°30'W., 6.5'
(rec. S.81°W., 6.6' per 1969 ren.)