

PRIMARY CORNER DESCRIPTION Cor. No. 6 HES 229

Alias	Description

HES No. 229 by Geo. W. Root, Forest Service Surveyor, under special instructions dated March 17, 1917 - Surveyed Oct. 1917 - DCSO records Vol. 28 Page(s) 12184)

Cor. No. 6 of listing survey, the marks of which I now destroy and in its place establish cor. No. of this survey, as follows: Mark a fir tree, 16" dia., 6 HES 229 on side facing the claim, for cor. No. 6 of this survey, from which

 A fir, 16" dia. bears N.42°15'W. 14 lks mkd X 6 HES 229 BT

 A fir, 20" dia. bears N.85°45'E. 13 lks mkd X 6 HES 229 BT

Raise a mound on earth, 4 ft. base, 2 ft. high, 3½ ft. dist., within the claim.

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9722-3

Cor. No. 6 HES No. 229, which is a fir, 18" dia., marked & witnessed as described in the official record.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 10/31/1969 - C.S. File 52/43-31

Found - Orig. 16", now 18" D.Fir corner tree, alive, shows good scar facing claim. Open & find "S22" scribe & reverse.

 Orig. 16", now 21" Fir, alive, N.42°15'W., 9.2 ft. shows good scar. Rescribe: "6 HES 229 CS BT"

 Orig. 20", now 22" Fir, alive, N.85°45'E., 8.6 ft. shows good scar. Rescribe: "6 HES 229 CS BT"

At a point 24" N.60°E., from center of corner tree

Set - 1" IP & brass cap mkd: "COUNTY SURVEYORS OFFICE 1969 T26S COR. #6 HES__ 229 R2E"

This corner lies on moderate NE slope.

Robert Dean - For: USFS - Dec. 1984 - M98-16 & C.S. 63/5-1

Found - 21" D.Fir per HES 229, "S2" visible, from which

 1" galvanized iron pipe, iron pipe,, with 2½" brass cap, (properly) mkd, (I add figures "✓ RM LS 1808" to cap) bears N.62°00'E., 1.70' (record N.60°E., 2.0 per 1969 ren.)

 A 23" D.Fir, healed scar, bears N.41°20'W., 10.7' (record N.42°15'W., 9.24' HES 229)

 A 23" D.Fir, healed scar, bears N.88°45'E., 10.0' (record N.85°45'E., 8.58' HES 229)