

PRIMARY CORNER DESCRIPTION Cor. No. 7 HES 229

Alias	Description
Alias	Description
Alias	Description
Alias	Description

HES No. 229 by Geo. W. Root, Forest Service Surveyor, under special instructions dated March 17, 1917 - Surveyed Oct. 1917 - DCSO records Vol. 28 Page(s) 12184)

Cor. No. 5 of listing survey, 50 ft. below cor. No. 6 of this survey. I destroy the listing corner and in its place establish cor. No. 7 of this survey as follows:
Set a cinder stone, 24x12x6", 14" in the ground, over a stone marked with a cross for cor. No. 7 of this survey, marked 7 HES 229 on side facing the claim, from which
 A pine, 8" dia. bears N.66°30'W. 56 lks mkd X 7 HES 229 BT
 A pine, 7" dia. bears S.45°45'W. 41 lks mkd X 7 HES 229 BT
Dig pits, 24x24x12", crosswise on this and the succeeding course, 7 ft. dist., and raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9723

Cor. No. 7 HES No. 229, which is a stone, 10x6x14" above ground, mkd and witnessed as described in the official notes.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 10/31/1969 - C.S. File 52/43-32

Found - Corner stone, in place, mkd: "X" on top & "7 HES229" on side facing claim.
 Orig. 8", now 26" Pine, alive, N.66½°W., 37.0 ft., shows scar, we tag.
 Orig. 7" now 24" Pine, alive, S.45°45'W., 27.1 ft., shows scar, we tag.
At point in place of Corner stone
Set - 1" IP & brass cap mkd. "COUNTY SURVEYORS OFFICE 1969 T26S COR #7 HES (229R2E)". Reset stone alongside.
New BTs- 15" Pine N.14°E., 31.9 ft. mkd: "7 HES 229 CS BT"
 15" Pine S.83°E., 39.0 ft. mkd: "7 HES 229 CS BT"
This corner lies in small grassy clearing about 100 ft in dia.

Robert Dean - For: USFS - Dec. 1984 - M98-16 & C.S. 63/5-1

Found - 1" galvanized iron pipe per 1969 ren., with 2½" brass cap, (properly) marked from which
 A 25" P.Pine, healed scar, bears S.47°05'W., 26.3' (rec. S.45°45'W., 27.06' per HES 229)
 A 28" P.Pine, healed scar, bears N.64°54'W., 37.3' (rec. N.66°30'W., 36.96' per HES 229)

continued next page

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 929070

PRIMARY CORNER DESCRIPTION Cor. No. 7 HES 229

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 17" P.Pine, healed scar, bears N.13°24'E., 31.7'
(rec. N.14°E., 31.9' per 1969 Ren.)
A 16" P.Pine, scribing visible, bears S.84°10'E.,
39.0' (rec. S.83°E., 39.0' per 1969 Ren.)