TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 942020

PRIMARY CORNER DESCRIPTION Cor. No. 2 HES 142

Alias 927020 Description Cor. No. 2 HES 227
Alias Description
Alias Description
Alias Description

---

HES No. 142 by Frank D. Maxwell, Forest Service Surveyor, under special instructions dated April 27, 1914 - Surveyed July 1914 - DCSO records Vol. 28 Page(s) 12165-6)

---

Cor. No. 2, 135 ft. above point of ascent, (or 235 ft. above cor. 1), identical with Cor. H/2 of listing survey, a fir tree, 28" dia., mkd. & witnessed as described by G.A. Bonebrake, Forest Ranger; I blaze & scribe the tree 2 HES 142 on SW face, for cor. 2, from which

A pine, 28" dia., bears S.17°15'W., 45 lks.
A fir, 30" dia., bears West, 76 lks.
Both trees blazed & scribed 2 HES 142 BT.

Pit and mounds impracticable at this and all other cors.

---

HES No. 227 by Geo. W. Root, Forest Service Surveyor, under special instructions dated March 14, 1917 - Surveyed Oct. 1917 - DCSO records Vol. 28 Page(s) 12179)

---

Cor. No. 2 of HES No. 142, heretofore described, 135 above point of ascent, also point for cor. No. 4 of list survey, which I establish as cor. No. 2 of this survey as follows: Mark a fir tree, 28" dia., 2 HES 227 on side facing the claim for cor. No. 2 of this survey; from which

A pine, 28" dia., bears S.18°15'W., 45 lks., mkd: X2 HES 227 BT.
A fir, 30" dia., bears N.89°00'W., 76 lks., mkd: X2 HES 227 BT.
Raise a mound of earth 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

---

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9723

---

Cor. No. 2 HES No. 142, common with cor. No. 2 HES No. 227, which is a fir, 32" dia., marked and witnessed as described in the official record.

---

Marvin C. Ramsey - For: J.H. Baxter & Co. - Witnesses: J. Goodin & R. Schultz - Sept. 12-22, 1960 - C.S. File 51/126

---

Found - D.Fir 32" with marks healed, from which Orig. BTs:
30" Y.Pine stump bears S.17¼°W., 45 lks., mkd: HES 227 BT.
30" D.Fir bears West 76 lks., down with marks burned out.

New BTs- 14" D.Fir bears N.20°W., 45 lks. mkd: 2 HES RS404 BT

continued next page

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 942020

PRIMARY CORNER DESCRIPTION Cor. No. 2 HES 142

Alias 927020 Description Cor. No. 2 HES 227
Alias Description
Alias Description
Alias Description

16" D.Fir bears S.14°E., 73 lks. mkd: 2 HES RS404 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 10/24/1969 - C.S. File 52/43-6

---

Found - Orig. 28" now 32" D.Fir corner Tree with healed blazes on SW & SE sides, also bark scribed "2 HES 142" on SW & "2 HES 227" on SE. Remains of orig. BTs still in evidence.
14" now 15" D.Fir, alive & in good condition, N.20°W., 29.7 ft.
16" now 15" D.Fir, alive, healed blaze, S.14°E., 48.2 ft. We tag.

Set - At base of corner tree on South side, brass cap mkd:
COUNTY SURVEYORS T26S R2E
OFFICE 1969 HES 142/HES 227

I. pipe & brass cap is 2.0 ft south of center of corner tree.

Robert Dean, LS 1808 - For: USFS - Dec. 20, 1984 - M98-6 & C.S. File 58/204-11

---

Found - 34" D. fir, 2 healed scars bark scribing "2HES 227", "2HES 142". From which:
A 1" galv. I.P. with 2½" brass cap bears S.37°00'W., 2.34 ft. (Rec. South 2.0 ft. per 1969 Ren.)
A 36" P.Pine stump, "2 HES 142 BT HES 227 BT" visible, bears S.17°00'W. 29.1 ft (Rec S.18°15'W. 29.70 ft. per HES 142)
A 60" D.Fir stump hole bears West 49.0 ft. (Rec. West 50.16 ft. per HES 142).
A 15" D.Fir healed scar bears N.22°10'E., 30.4 ft. (Rec. N.20°W 29.70 ft. per 1960 & 1969 Renewals)
A 17" D.Fir healed scar, bears S.13°30'E., 48.3 ft. (Rec. S.14°E., 48.18 ft. per 1960 Ren.)

I ADD: Figures "↗ RM LS 1808" to brass cap.