

PRIMARY CORNER DESCRIPTION Cor. No. 3 HES 142

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>HES No. 142 by Frank D. Maxwell, Forest Service Surveyor, under special instructions dated April 27, 1914 - Surveyed July 1914 - DCSO records Vol. 28 Page(s) 12166)</p> <p>-----</p> <p>Cor. No. 3, 40 ft. above ravine, identical with cor. H/3 of listing survey, a post, mkd. and witnessed as described by G.A. Bonebrake, Forest Ranger; in place of which I set a basalt stone, 24x12x7", 14" in the ground, for Cor. 3 mkd. 3 HES 142 on E face, with a cross (+) on top, from which</p> <ul style="list-style-type: none"><li>A pine, 6" dia., bears S.16°30'E., 53 lks.</li><li>A pine, 36" dia., bears S.18°40'W., 160 lks.</li></ul> <p>Both trees blazed &amp; scribed 3 HES 142 BT.</p> <p>Pit and mounds impracticable at this and all other cors.</p>
<p>GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9724</p> <p>-----</p> <p>Cor. No 3 HES No. 142 which is a stone, 10x6x8" above ground, marked &amp; witnessed as described in the official record.</p>
<p>Marvin C. Ramsey - For: J.H. Baxter &amp; Co. - Witnesses: J. Goodin &amp; R. Schultz - Sept. 12-22, 1960 - C.S. File 51/126</p> <p>-----</p> <p>Found - Corner is monumented with a basalt stone 12x7x7" above the ground, mkd. X on top, 3 HES 142 on the side facing the claim, from which the only extant Orig. BT:</p> <ul style="list-style-type: none"><li>22" Y. Pine bears S.16½°E., 53 lks., healed.</li></ul> <p>New BT - D.Fir 18" bears N.22°E., 79 lks. mkd. 3 HES 142 RS404 BT.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - Oct. 27, 1969 - C.S. File 52/43-11</p> <p>-----</p> <p>Found - Orig. corner stone, in place, mkd: "X" on top with "HES 142" on side.</p> <ul style="list-style-type: none"><li>Orig. 6", now 24" Y.Pine, alive, S.16½°E., 35.0 ft. healed blaze. Rescribe: "3 HES 142 CS BT"</li><li>18" D.Fir N.22°E., 52.1 ft. alive, blaze healed, we tag. 1960</li></ul> <p>Set - At cor. point in place of stone, 1" IP &amp; Brass cap mkd: COUNTY SURVEYORS OFFICE 1969 T26S #3 HES 142 R2E" reset cor. stone alongside</p> <p>This corner lies on moderate SE slope.</p>
<p>continued next page</p>

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 942030

PRIMARY CORNER DESCRIPTION Cor. No. 3 HES 142

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Robert Dean, LS 1808 - For: USFS -Dec. 20, 1984 - M98-6 & C.S. File 58/204-11

-----  
Found - 1" galvanized iron pipe with 2½" brass cap  
(properly) marked, 1969, from which  
A 12"x16" sandstone, mkd "3HES142" lies east 0.5'±.  
A 28" Pond. Pine, scribing visible, bears S.15°30'E.  
34.7' (rec. S.16°30'E., 34.98' per HES 142)  
A 20" D.Fir, healed scar, bears N.22°10'E., 51.8'  
(rec. N.22°E., 52.14' per 1960)