

PRIMARY CORNER DESCRIPTION Cor. No. 4 HES 142

| Alias | Description |
|-------|-------------|
| | |
| | |
| | |
| | |

HES No. 142 by Frank D. Maxwell, Forest Service Surveyor, under special instructions dated April 27, 1914 - Surveyed July 1914 - DCSO records Vol. 28 Page(s) 12166)

Cor. 4, identical with cor. H/4 of listing survey, a post mkd. and witnessed as described by G.A. Bonebrake, Forest Ranger, in place of which, I set a basalt stone, 24x14x8", 14" in the ground, for Cor. 4, mkd. 4 HES 142 on NE face, with a cross (+) on top, from which

- A fir, 6" dia., bears N.22°10'E., 135 lks.
- A fir, 30" dia., bears S.37°30'E., 185 lks.

Both trees blazed & scribed 4 HES 142 BT.
Pit and mounds impracticable at this and all other cors.

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9724

Cor. No. 4 HES No. 142, which is a stone, 14x8x10" above ground, mkd & witnessed as described in the official record.

Marvin C. Ramsey - For: J.H. Baxter & Co. - Witnesses: J. Goodin & R. Schultz - Sept. 12-22, 1960 - C.S. File 51/126

Found - Corner is monumented with a basalt stone 12x8x8" above the ground, mkd. X on top, 4 HES 142 on the side facing the claim, from which the orig. BTs:

- 18" D.Fir stump bears N.22°10'E., 135 lks., with blaze healed.
- 34" D.Fir bears S.37½°E., 185 lks. with blaze healed

New BT - 16" D.Fir bears S.62°W., 12 lks., mkd: 4 HES 142 RS404 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - Oct. 27, 1969 - C.S. File 52/43-12

Found - Orig. corner stone, in place, & mkd: "X" on top with "HES 142" facing claim.

- Orig. 30" now 36" D.Fir, alive, S.37½°E., 122.1 ft. shows good scar. We tag.
- Orig. 6" now 18" Fir N.22°10'E., 89.1 ft. now stump. We open & find scribe.

1960 BT- 16" D.Fir S.62°W., 7.9 ft. alive, healed blaze. We tag.

Set - At corner point in place of stone, set 1" I.P. & brass cap mkd: "COUNTY SURVEYORS OFFICE 1969 T26S COR. #4 \HES R2E" Reset old cor. stone alongside brass cap. continued next page

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 942040

PRIMARY CORNER DESCRIPTION Cor. No. 4 HES 142

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

New BT - 8" D.Fir N.28°E., 19.4 ft. mkd: "4 HES 142 CS BT"
This corner lies about 10.83 chs Westerly of cor. #5 HES #142

Robert Dean, LS 1808 - For: USFS - Dec. 20, 1984 - M98-6 & C.S. File 58/204-11

Found - 1" galvanized iron pipe with 2½" brass cap, (properly) marked per 1969 ren., in 24" cairn, from which
A 38" D.Fir, healed scar, bears S.38°E., 122.1' (rec. S.37°30'E. 122.1' per HES 142)
An 18" rotted stump, "4 HES 142 BT" visible, bears N.22°E. 89.3' (rec N.22°10'E. 89.10' per HES 142)
A 9" D.Fir, scribing visible, bears N.26°45'E., 19.4' (rec. N.28°E., 19.4' per 1969 ren)
A 17" D.Fir, healed scar, bears S.62°W., 8.1' (rec. S.62°W., 7.92' per 1960 ren.)
Cairn built to 36"