

PRIMARY CORNER DESCRIPTION Cor. No. 2 HES 178

Alias	Description
Alias	Description
Alias	Description
Alias	Description

HES No. 178 by Frederick W. Rase, Forest Service Surveyor, under special instructions dated December 17, 1915 - Surveyed Aug. 1916 - DCSO records Vol. 28 Page(s) 12169)

 Cor. No. 2, identical with cor. No. 1 of listing survey and SW cor. of Illahee Ranger Station, which I destroy and in its place. Set a lava stone, 26x12x10", 16" in the ground, over a stone mkd. with a cross for cor. No. 2 of this survey, mkd. 2 HES 178 on side facing the claim, from which
 A pine, 8" dia., bears S.44°45'E., 117 lks. marked X 2 HES 178 BT.
 A pine, 12" dia., bears N.21°15'E., 243 lks., marked X 2 HES 178 BT.
 Raise a mound of stone, 3 ft. base, 2 ft. high, 3½ ft. dist., within the claim.
 Note - See C.S. 63/5 for copy of "Listing Survey"notes.

 GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9726

 Cor. No. 2 HES No. 178, which is a stone, 10x6x8" above ground, marked & witnessed as described in official record.

 Douglas Co. Surveyors Office - B.B. Irving, Co. Surveyor - July 1945 - M12-40

 1" Drill steel & rock (Original) Witness trees gone.

 Robert L. Dean, LS 1808 - For: USFS - January 18, 1985 - M98-20 & C.S. File 63/5-2

 Obliterated corner restored in orig. location according to:
 1) Testimony of property owner Mr. John Aymond, who remembers that the drill steel mentioned in M12-40 used to lie under a fence which ran north/south on the west side of the old road. He showed me the stumps of the old fence posts sawed off at ground level.
 2) The record bearing & distance from the stump of a BT of the 1913 listing survey
 Set - 2"x30" magnetic aluminum monument in 36" cairn, mkd "T26S R2E 2HES178 (LS1808 1985" from which:
 1"x29" bent drill steel per M12-40 lying, loosely, pointed in north/south direction, covered by 1" of soil & turf, bears N.85°W. 0.2' from corner location. The drill steel is now placed inside the new monument
 continued next page

PRIMARY CORNER DESCRIPTION Cor. No. 2 HES 178

Alias	Description
Alias	Description
Alias	Description
Alias	Description

60" P.Pine sawed stump, no marks, bears S.2°15'E., 402.60' (rec. S.2°15'E., 402.60' per listing survey)
New BTs- 11" W.Oak, scribed "2HES178BT" bears N.49°45'E., 311.7'
17" D.Fir, scribed "2HES178BT", bears S.13°00'E., 374.8'
A 3/4" brass disc stamped "RLS 1808" is nailed low to the face of each new BT.

Leonard E. Herzstein, USFS - July thru Nov. 2001 - C.S. File 65/41-1

I find a 2½" outside diameter alum. post, firmly set in concrete, flush with a 3 ft. dia., mound of stone, with a 2½" dia., magnetized alum. cap attached, properly mkd.
From which the BTs mkd. by Dean in 1985:
A 12" W.Oak bears N.49°45'E., 311.7 ft. (95.01 m.) (rec. N.49°45'E., 311.7 ft.) with a healed blaze.
A 22" D.Fir bears S.13°00'E., 374.8 ft. (114.24 m.) (rec. S.13°00'E., 374.8 ft.) with a healed blaze.
From which I tie new accessories:
A fd. 6" dia., wood fence corner bears S.88°00'W., 0.7 ft. (0.23 m.) projecting 5 ft. above the ground, set in concrete.
A fd. telephone box bears N.33°30'W., 45.8 ft. (13.95 m.) projecting 3 ft. above the ground.
The corner is in the middle of Illahee Flats meadow under a new electric fence line.