

PRIMARY CORNER DESCRIPTION Cor. No. 3 HES 178

Alias	Description
Alias	Description
Alias	Description
Alias	Description

HES No. 178 by Frederick W. Rase, Forest Service Surveyor, under special instructions dated December 17, 1915 - Surveyed Aug. 1916 - DCSO records Vol. 28 Page(s) 12170

-----

Cor. No. 3 (60 ft. below flat) identical with cor. No. 2 of listing survey, which I destroy, and in its place.  
Set a lava stone, 30x9x9", 20" in the ground, over a stone mkd. with a cross for cor. No. 3 of this survey, mkd. 3 HES 178 on side facing the claim; from which

- A fir, 14" dia., bears N.83°15'E., 117 lks., mkd. X 3 HES 178 BT"
- A pine, 40" dia., bears S.27°45'W., 90 lks., mkd. X 3 HES 178 BT.

Raise a mound of stone, 3 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

Note - See C.S. 63/5 for copy of "Listing Survey"notes.

---

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9726

-----

Cor. No. 3 HES No. 178, which is a stone, 7x8x8" above ground, marked & witnessed as described in the official record.

---

Douglas Co. Surveyors Office - B.B. Irving, Co. Surveyor - July 1945 - M12-40

-----

Pine BT gone. Found corner as recorded in the official Government field notes. Blazed

- A 10" Fir N.17¾°W., 15.4 ft. Cor. No. 3 HES 178 CSBT

---

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 10/28/1969 - C.S. File 52/43-17

-----

Found - Corner stone, in place & mkd: "3 HES 178" on side & "X" on top.

- Orig.? 14" now 40" D.Fir, alive, N.83°15'E., 77.2 ft. shows good scar - we tag.
- 1945 BT: 10", now 18" D.Fir, alive, N.17¾°W., 15.4 ft., shows very good scar - we tag.

At corner point, in place of stone:

Set - A 1" IP & Brass cap at cor. mkd: COUNTY SURVEYORS 1969 T26S COR. #3 HES    178 R2E"

New - 13" D.Fir N.54°W., 7.1 ft. mkd: "3 HES 178 CS BT"

This cor. lies on steep, southerly slope about 100' S of old Illahee Guard Station Road.

Cont.

PRIMARY CORNER DESCRIPTION Cor. No. 3 HES 178

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Robert L. Dean, LS 1808 - For: USFS - January 18, 1985 - M98-20 & C.S. File 63/5-2

-----  
Found - 1" galv. iron pipe with 2½" brass cap, (properly) marked, in 36" cairn, per 1969 ren., from which  
42" D.Fir, healed scar, bears N.83°30'E., 75.0' (rec. N.83°15'E., 77.22', per HES 178)  
15" P.Pine, healed scar, bears S.47°30'E., 26.1' (rec. S.50°E., 29.70' per listing survey)  
50" Y.Pine, stump hole bears S.62°15'W., 83.4' (rec. 30" S.61°W., 81.84' per listing survey)  
16" D.Fir, healed scar, bears N.54°45'W., 6.7' (rec. N.54°W., 7.1' per 1969 ren.)  
19" D.Fir, healed scars, bears N.16°15'W., 15.3' (rec. N.17°45'W., 15.4' per 1945)

Leonard E. Herzstein, USFS - Chris Sturman, witness - 10/22/2001 - C.S. File 65/40-8

-----  
Found a 1" iron pipe with 2½" brass cap established by Tracy in 1969, properly marked, firmly set in concrete, projecting 12" above a 2-foot diameter mound of stone.

From which the remaining original bearing tree: A 46" D.Fir, bears N.83°30'E., 76.4 feet (rec. N.83°15'E., 77.22 ft., Rase, 1916, and N.83°30'E. 75.0 ft., Dean, 1985), with a healed blaze.

From which the remains of the listing survey bearing tree:  
A roothole bears S. 47°30' E., 26.1 feet (rec. S.50°E., 29.70 ft., listing survey, 1913, & S.47°30'E., 26.1 ft., Dean, 1985), with downed 16" ponderosa pine alongside with healed blaze.

And from which the following bearing tree marked by Irving in 1945:

A 20" D.Fir stump, bears N.13°W., 15.3 feet (rec. N.17¾°W., 15.4 ft., Irving, 1945, and N.16°15'W. 15.3 ft., Dean, 1985), with healed blaze.

And from which the following bearing tree marked by Tracy in 1969:

A 16" D.Fir stump, bears N.54°45'W., 6.7 feet (rec. N.54°W., 7.1 ft. Tracy, 1969, & N.54°45'W., 6.7 ft. Dean, 1985), with healed blaze.

I mark new accessories for the corner:

A steel fence post, bears N.7°30'W. 3.4 ft. projecting 4 feet above the ground, with Forest Service "Property Boundary" sign attached.

continued next page

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 978030

PRIMARY CORNER DESCRIPTION Cor. No. 3 HES 178

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

An 18" D.Fir, bears S.27°30'W., 29.0 feet, scribed "HES 178 3 BT" on a single blaze with a ¾" brass washer stamped "LS 2150" nailed to the face of the blaze.

A steel fence post, bears N.74°30'W., 3.2 ft., projecting 4 ft. above the ground, with Forest Service "Property Boundary" and "Land Survey Monument" signs attached.

A 6" diameter wood fence corner, bears N.3°30'W., 0.7 ft., 4 ft. above the ground, set in concrete.

Bearings are based on S.7°24'E., for the line between corners 2 & 3 & reported to the nearest 15 minutes. Tree measurements are to the center of the root crown. Tree diameters are at breast height.