

PRIMARY CORNER DESCRIPTION Cor. No. 4 HES 178

Alias	Description
Alias	Description
Alias	Description
Alias	Description

HES No. 178 by Frederick W. Rase, Forest Service Surveyor, under special instructions dated December 17, 1915 - Surveyed Aug. 1916 - DCSO records Vol. 28 Page(s) 12170)

Cor. No. 4, identical with cor. No. 3 of listing survey which I destroy and in its place Set a lava stone, 24x10x8", 14" in the ground, over a stone mkd. with a cross for cor. No. 4 of this survey, mkd. 4 HES 178 on side facing the claim; from which

An Oak, 14" dia., bears N.74°00'W., 128 lks. marked X 4 HES 178 BT.

A pine, 14" dia., bears N.75°15'E., 23 lks., marked X 4 HES 178 BT.

Raise a mound of earth 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

Note - See C.S. 63/5 for copy of "Listing Survey"notes.

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9726

Cor. No. 4 HES No. 178, which is a stone, 4x10x8" above ground, mkd & witnessed as described in the official record.

Douglas Co. Surveyors Office - B.B. Irving, Co. Surveyor - July 1945 - M12-40

Found rock displaced. Replaced in orig. location from both orig. BTs. Drove 5/8"x24" IR alongside, top flush with ground

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 10/28/1969 - C.S. File 52/43-14

Found - Orig. 14" now 20" oak N.74°W., 84.5 ft. alive, faint scribe marks visible on unhealed blaze.

Orig. 14" now 36" Pine N.75°15'E., 15.2 ft. now stump - blaze visible on top.

We do not find I. Rod called for in 1945 ren. Old corner stone broken in 2 pieces with marks "4 HES 178" on smaller piece - at point:

Set - 1" IP & brass cap mkd: COUNTY SURVEYORS OFFICE 1969 T26S COR. #4 |HES 178 R2E and reset cor. stone pieces along side brass cap & mkd.

New BTs- 18" Y.Pine S.76½°E., 88.1 ft. mkd. "4 HES 178 CS BT"  
16" D.Fir S.83°W., 77.2 ft. mkd. "4 HES 178 CS BT"

This corner lies 8.0 ft. N of fence, course Easterly & Westerly.

Cont.

PRIMARY CORNER DESCRIPTION Cor. No. 4 HES 178

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Robert L. Dean, LS 1808 - For: USFS - January 18, 1985 - M98-20 & C.S. File 63/5-2

-----  
Found - 1" galv. iron pipe with 2½" brass cap, (properly) marked, per 1969 ren, from which:  
A 12"x10"x5" cinder stone marked "4HES178" lies East 0.5'±;  
Pitched center of Y.Pine stump "S178BT" visible at 8" from center, bears N.78°30'E., 15.0' (rec. N.75°15'E., 15.18' per HES 178)  
24" P.Pine, healed scar, bears S.78°00'E., 87.9' (rec. S.76°30'E., 88.1' per 1969 ren)  
25" D.Fir, healed scar, bears S.81°30'W., 77.4' (rec. S.83°W., 77.2' per 1969 ren.)  
18" W.Oak, rotted face, N.74°50'W., 84.5' (rec. N.74°00'W., 84.48' per HES 178)

Leonard E. Herzstein, USFS - Chris Sturman & Katie Tobel, witnesses - 10/29/2001 - C.S. File 65/40-9

-----  
Found: 1 " iron pipe with 2½" brass cap established by Tracy in 1969, properly marked, firmly set in concrete, projecting 12" above ground. The remains of the orig. corner stone are now scattered on the ground. I place a 3 ft. dia. mound of stone around the iron pipe, which now projects 4".  
From which the remaining original bearing trees:  
8" remains of ponderosa pine stump, bears N.79°E. 14.7 ft (rec. N.75°15'E. 15.18 ft., Rase, 1916, & N.78°30'E., 15.0 ft., Dean, 1985), with scribe marks "S 178" visible on previously opened blaze.  
A 18" white oak, bears N.74°45'W., 84.0 ft (rec. N.74°W., 84.48 ft., Rase, 1916, & N.74°50'W., 84.5 ft., Dean, 1985), with decayed face on a partially healed blaze.  
And from which the following bearing trees marked by Tracy in 1969:  
A 28" P.Pine stump, bears S.78°E. 88.1 ft (rec. S.76½° E. 88.1 ft. Tracy, 1969, & S.78°00'E., 87.9 ft., Dean, 1985), with healed blaze.  
A 36" Douglas fir, bears S.81°30'W., 76.4 feet (rec. S.83°W., 77.2 ft., Tracy, 1969, & S.81°30'W., 77.4 ft., Dean, 1985), with healed blaze.  
I mark new accessories for the corner: .  
A steel fence post, bears S.74°30'E., 3.8 feet, projecting 3.5 feet above the ground, with Forest Service "Property Boundary" and "Land Survey Monument" signs attached.  
An 8" D.Fir , bears S.52°30'E., 29.8 feet, scribed "4-178 BT" on a single blaze with a ¾" brass washer stamped "LS 2150" nailed to the face of the blaze.

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 978040

PRIMARY CORNER DESCRIPTION Cor. No. 4 HES 178

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 6" diameter wood fence corner, bears N.11°15'W., 0.4 feet, projecting 4 feet above the ground, set in concrete. Bearings are based on S.74°37'E. for the line between corners 4 and 3 per M98-20 and reported to the nearest 15 minutes. Tree measurements are to the center of the root crown. Tree diameters are at breast height.