

PRIMARY CORNER DESCRIPTION Cor. No. 5 HES 178

Alias	Description
Alias	Description
Alias	Description
Alias	Description

HES No. 178 by Frederick W. Rase, Forest Service Surveyor, under special instructions dated December 17, 1915 - Surveyed Aug. 1916 - DCSO records Vol. 28 Page(s) 12170

Cor. No. 5, identical with cor. No. 4 of listing survey, which I destroy and in its place.

Set a granite stone 26x15x10" 16" in the ground, over a stone mkd. with a cross for cor. No. 5 of this survey, mkd. 5 HES 178 on side facing the claim; from which

A pine, 40" dia., bears S.29°30'W., 41 lks. marked X 5 HES 178 BT.

A tamarack, 24" dia., bears N.46°45'E., 100 lks. marked X HES 5 178 BT.

Raise a mound of earth 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

Note - See C.S. 63/5 for copy of "Listing Survey" notes.

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9726

Cor. No. 5 HES No. 178, which is a stone, 15x10x12" above ground, mkd & witnessed as described in the official record

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 10/29/1969 - C.S. File 52/43-20

Found - No trace of corner stone.

Orig. 40", now 42" Pine snag, S.29½°W., 27.1 ft., scribe visible on unhealed blaze.

Orig. 24", now 36" D.Fir (Rec. Tamarack) alive, N.46°45'E., 66.0 ft. shows good scar, we tag.

At corner point

Set - 1" I.P. & brass cap mkd. "COUNTY SURVEYORS OFFICE 1969 T26S COR. #5 HES 178 R2E"

New BTs- 8" W.Fir S.43°E., 6.9 ft. mkd: "5 HES 178 CS BT".

13" D.Fir S.25°W., 12.0 ft. mkd: "5 HES 178 CS BT".

This corner lies in power line clearing about 100 ft. E. of a 48" D.Fir, #115, that has power line attached. Line course S.80°E. - N.80°W.

Robert L. Dean, LS 1808 - For: USFS - January 18, 1985 - M98-20 & C.S. File 63/5-2

Found - 1" galv. iron pipe with 2½" brass cap, (properly) mkd per 1969 ren. from which

37" D.Fir, healed scar, bears N.46°30'E., 64.6' (rec. N.46°45'E., 66.00 per HES 178) cont.

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 978050

PRIMARY CORNER DESCRIPTION Cor. No. 5 HES 178

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

12" W.Fir, healed scar, bears S.42°30'E., 7.0' (rec. S.43°E., 6.9' per 1969 ren.)
14" D.Fir, healed scar, bears S.24°15'W., 12.0' (rec S.25°W., 12.0' per 1969 ren.)
36" P.Pine snag, scribing visible in rotted face, bears S.30°00'W., 26.9' (rec. S.29°30'W., 27.06' per HES 178)