



TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 978070

PRIMARY CORNER DESCRIPTION Cor. No. 7 HES 178

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From which the following accessories marked by Tracy in 1969:

A 1" iron pipe, bears S.17°W., 2.0 ft. (rec. 2.0 ft., Tracy, 1969, and S.12°12'W., 2.22 ft., Dean, 1985), with 2½" brass cap marked as shown, firmly set, projecting 15" above a 1 ft. dia. mound of stone. I make a 3- foot dia. mound of stone around the iron pipe, which now projects 4".

A 12" D.Fir stump, bears S.45°45'W., 16.0 ft. (rec. S.47°W., 16.4 ft., Tracy, 1969 & S.44°00'W., 16.0 ft., Dean, 1985), with healed blaze.

I mark new accessories for the corner:

A 14" D.Fir, bears N. 61°E., 20.5 ft., scribed "7 BT" on a single blaze with a ¾" brass washer stamped "LS 2150" nailed to the face of the blaze.

A steel fence post, bears S.85°30'E., 2.7 ft., projecting 5 ft. above the ground, with Forest Service "Property Boundary" and "Land Survey Monument" signs attached.

A 6" dia. wood fence corner, bears S.79°W. 3.3 ft. projecting 4 feet above the ground, set in concrete.

A 13" D.Fir, bears N.01°30'W., 9.3 ft., scribed "7-178 BT" on a single blaze with a ¾" brass washer stamped "LS 2150" nailed to the face of the blaze.

Bearings are based on S.85°38'E. for the line between corners 7 and 1 per M98-20 and reported to the nearest 15 minutes. Tree measurements are to the center of the root crown. Tree diameters are at breast height.