

PRIMARY CORNER DESCRIPTION Cor. No. 1 HES #182

Alias	Description

HES No. 182 by Frederick W. Rase, Forest Service Surveyor, under special instructions dated January 7, 1916 - Surveyed Aug. 1916 - DCSO records Vol. 28 Page(s) 12174)

-----  
Begin at cor. No. 1 of this survey, identical with cor. No. 1 of listing survey and Forest Service monument, which is a D.Fir tree 36" dia. I obliterate all listing survey marks and mark the tree 1 HES 182 on side facing the claim, from which  
    A pine, 42" dia., bears N.3°15'E., 152 lks., mkd: X 1 HES 182 BT.  
    A pine, 32" dia., bears N.13°45'E., 191 lks., mkd: X 1 HES 182 BT.  
Raise a mound of earth, 4 ft. base, 2 ft. high, 3½ ft. dist. within the claim.  
    USLM No. 142 bears S.84°25'E., 158.19 chs (described in field notes of HES #93)  
    Cor. No. 5 HES No. 93 (accepted) bears N.74°30'E., 22.40 chs. (direct measurement)  
    Cor. No. 5 of HES No. 178, surveyed by me, bears S.68°53'E., 85.95 chs. (direct measurement)

-----  
GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9729-30

-----  
HES 182 retracement  
Cor. No. 1 HES No. 182, which is a fir, 40" marked and witnessed as described in the official record.

-----  
Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - Oct. 30, 1969 - C.S. File 52/43-23

-----  
Found - Orig. 36", now 48" D.Fir Corner Tree, alive, shows good scar facing claim.  
    Orig. 42" Pine, now only partial burned out stump, N.3°15'W. 100.3 ft. scribe marks visible on burned blaze.  
    Orig. 32" now 40" Pine, alive, N.13°45'E., 126.1 ft. scribe visible on unhealed & burned blaze. We tag  
Set - Brass cap 4 ft. N.45°W., of center of cor. tree mkd;  
    County Surveyors T26S R2E  
    Office 1969 COR. #1 HES 182  
New BT- 8" D.Fir N.41°W. 29.5 ft. mkd: "1 HES 182 CS BT"  
    13" D.Fir S.84°W.,   ? ft. mkd: "1 HES 182 CS BT"  
This corner lies on S.E. slope. Bear & Dists from old Corner Tree.

continued next page

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 982010

PRIMARY CORNER DESCRIPTION Cor. No. 1 HES #182

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Robert Dean, LS 1808 - For: USFS - Nov. 11, 1984 - M97-60 & C.S. File 58/204

-----  
Found - 42" D.Fir, good scar, facing N.55°W., from which:  
a 1" galv. I.P. with 2½" brass cap, properly mkd.,  
bears N.55°00'W. 4.00 ft (Rec N.45°W., 4 ft) 1969  
A 50" P.Pine, burnt and rotted stump bears  
N.3°45'W., 100.5 ft. (Rec. N.3°15'W., 100.32 ft.)  
A 38" P.Pine, scribing visible, bears N.12°15'E.,  
127.6' (Rec. N.13°45'E., 126.06 ft.)  
A 16" D.Fir, good scar, bears S.83°45'W., 36.8 ft.  
(Rec. S.84°W., 26.4 ft.) 1969  
A 13" D.Fir, good scar, bears N.42°30'W., 27.3 ft.  
(Rec. N.41°W., 29.5 ft.) 1969

I add figures to cap which now appears as shown;  
County Surveyors Office

T26S R2E  
H.E.S. | RM  
182 | LS 1808  
COR #1  
S55°E  
↙  
4 ft  
1969