

PRIMARY CORNER DESCRIPTION Cor. No. 3 HES #182

Alias	Description

HES No. 182 by Frederick W. Rase, Forest Service Surveyor, under special instructions dated January 7, 1916 - Surveyed Aug. 1916 - DCSO records Vol. 28 Page(s) 12175)

-----

Cor. No. 3 (40 ft. below top of ascent) identical with cor. No. 3 of listing survey, which I destroy and in its place Set a basalt stone 24x13x7", 14" in the ground, over a stone mkd. with a cross for cor. No. 3 of ths survey, mkd. 3 HES 182 on side facing the claim, from which

- A fir, 18" dia., bears S.39°30'W., 43 lks., marked X 3 HES 182 BT.
- A fir, 12" dia., bears S.60°45'E., 57 lks., marked X 3 HES 182 BT.

Raise a mound of earth 4 ft. base, 2 ft. high, 3½ ft. within the claim.

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9730

-----

Cor. No. 3 HES No. 182, which is a stone, 12x7x9" above ground, marked and witnessed as described in the official record.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 10/30/1969 - C.S. File 52/43-24

-----

Found - Corner Stone, in place, mkd: "3 HES 182" on side facing claim.

- Orig. 18", now 26" Fir Stump, cut low, S.39°30'W., 28.4 ft., no scribe.
- Orig. 12", now 22" Fir Stump, cut through middle of blaze, S.60°45'E., 37.6 ft., scar shows plainly.

Set - Brass Gap at Cor. Mkd: County Surveyors T26S R 2 E (Reset Stone Alongside) Office, 1969 Cor. #3 HES 182

New BTs- 12" Maple S.84°E. 12.3 ft. mkd: "3 HES 182 CS BT".  
12" D.Fir N.3°E., 25.5 ft. mkd: "3 HES 182 CS BT".  
12" D.Fir N.80°W., 22.5 ft. mkd: "3 HES 182 CS BT".

This corner lies on very steep, westerly slope.

Robert Dean, LS 1808 - For: USFS - Nov. 11, 1984 - M97-60 & C.S. File 58/204-10

-----

Found - 1" galvanized iron pipe with 2½" brass cap, (properly) marked (per 1969 Ren.) in small cairn, from which:

continued next page

