TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 993010

PRIMARY CORNER DESCRIPTION Cor. No. 1 HES 93

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

HES No. 93 by Frank D. Maxwell, Forest Service Surveyor, under special instructions dated July 7, 1913 - Surveyed July 1914 - DCSO records Vol. 28 Page(s) 12160)

Cor. No. 1, identical with Cor. H/9 of listing survey, a stone, Mkd. and witnessed as described by Asher Ireland, Assistant Forest Ranger, in place of which I set a basalt stone, 24x10x8", 14" in the ground for Cor. No. 1, Mkd. HES 93 on W face, with a cross (+) on top; from which
A fit, 30" dia., bears N. 38°30' E., 94 lks.
A fir, 36" dia., bears S.11°45'E., 63 lks.
Both trees blazed and scribed 1 HES 93 BT.
Pits & mound impracticable at this and all other courses.

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9727

Cor. No. 1 HES No. 93, which is a stone, 8x8x10" above ground, firmly set, marked & witnessed as described in the official record.

Marvin C. Ramsey - For: J.H. Baxter & Co. - Witnesses: J. Goodin & R. Schultz - Sept. 12-22, 1960 - C.S. File 51/126

Corner common with A P 1 Bates Tract.
The corner stone has been disturbed by the construction of a power line; determined the corner point from the Orig. BTs:
32" D.Fir sawed stump bears N.38½°E., 94 lks. with partial scribe marks.
36" D.Fir sawed stump bears S.11¾°E., 63 lks., I open & find mkd. BT.
Set an IP 3' long 1½" dia 28" in the gr mkd RS404 from which:
14" Y.Pine bears N.7½°E., 133 lks. mkd. 1 HES 93 RS404 BT.
16" D.Fir bears S.9°W., 164 lks., mkd. 1 HES 93

Robert Dean, LS 1808 - For: USFS - Jan. 25, 1985 - M98-27 & C.S. File 63/5-3

Found - Corner location by intersection of distances from orig. BT stumps.
Set - 2"x30" magnetic alum. monument, mkd: "LS1808 HES 93 T26S R2E 1985", in 36" cairn, from which
Fd. 1¼"x32" galv. iron pipe per 1960 ren. with 3/4" brass disc stamped "RS 404" inside, lying loose N.65°42'W., 1.08'. I place this pipe inside the new monument;

continued next page

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 993010

PRIMARY CORNER DESCRIPTION Cor. No. 1 HES 93

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

20" P.Pine, healed scar, N.6°35'E., 88.3' (rec. N.7½°E., 87.78' per 1960 ren.)
42" D.Fir rotted stump in road fill, "93" visible at 14" center, N.37°15'E., 62.04' (rec. N.38°30'E., 62.04' per HES 93)
36" D.Fir stump, S.12°10'E., 41.58' (rec. S.11°45'E., 41.58' per HES 93)
22" D.Fir, healed scar, S.9°30'W., 107.0' (rec. S.9°W., 108.24' per 1960 ren.)
46" rotted Pine stump, N.79°45'W., 72.0' (rec. N.78°W., 76.56' per listing survey)