

PRIMARY CORNER DESCRIPTION Cor. No. 2 HES 93

Alias	Description
Alias	Description
Alias	Description
Alias	Description

HES No. 93 by Frank D. Maxwell, Forest Service Surveyor, under special instructions dated July 7, 1913 - Surveyed July 1914 - DCSO records Vol. 28 Page(s) 12160

Cor. No. 2, identical with Cor. H/1 of listing survey, a fir tree 36" dia. mkd. and witnessed as described by Asher Ireland, Assistant Forest Ranger. I mark the tree 2 HES 93 on N face for Cor. 2, from which
 A fir, 32" dia., bears S.88°00'E., 105½ lks.
 A fir, 32" dia., bears S.21°30'E., 100 lks.
 A fir, 24" dia., bears S.14°15'W., 68 lks.
 A fir, 20" dia., bears N.74°30'W., 73 lks.
Each tree mkd: 2 HES 93 BT.

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9727

Cor. No. 2 HES No. 93, a fir, 40" dia., marked & witnessed as described in the official record.

Marvin C. Ramsey - For: J.H. Baxter & Co. - Witnesses: J. Goodin & R. Schultz - Sept. 12-22, 1960 - C.S. File 51/126

The corner point is determined from the only extant orig. BT:
 40" D.Fir bears S.88°E., 105½ lks, I open & find "B" leave other mks. healed.
Set - an IP 3' long 1½", 3" below the surface of road bed from which:
 24" D.Fir bears N.8½°W. 95 lks. mkd. 2 HES 93 RS404 BT.
 10" D.Fir bears N.69°E. 61 lks. mkd. 2 HES 93 RS404 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - 11/1969 - C.S. File 52/43-34

1½" IP & OBT & New BT.
New BT to NW gone completely.
IP is in "Y" of driveway. North 31.0' of edge of pavement of North Umpqua Hwy. See sketch in file.

Robert Dean, LS 1808 - For: USFS - Jan. 25, 1985 - M98-27 & C.S. File 63/5-3

Found - 1½" iron pipe per 1960 ren., 6" deep in driveway; from which;

continued next page

1

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 993020

PRIMARY CORNER DESCRIPTION Cor. No. 2 HES 93

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

55" D.Fir, healed scar, bears S.87°45'E., 70.3'
(rec. S.88°E., 69.63' per HES 93)
20" D.Fir, healed scar, bears N.69°00'E., 40.4'
(rec. N.69°E., 40.26' 1960 ren)
New RM - Set a 2"x30" magnetic alum. monument mkd: "LS1808 RM
2 HES 93 √ S55°W ↙ 25 ft T26S R2E 1985" in 36"
cairn N.55°17'E., 25.00'