

PRIMARY CORNER DESCRIPTION Cor. No. 3 HES 93

Alias	Description
Alias	Description
Alias	Description
Alias	Description

HES No. 93 by Frank D. Maxwell, Forest Service Surveyor, under special instructions dated July 7, 1913 - Surveyed July 1914 - DCSO records Vol. 28 Page(s) 12160-1)

-----

Cor. No. 3, identical with cor. H/2 of listing survey, a basalt boulder, (in place), 5 ft. NE & SW, 3 ft. NE & SE, 1 ft. high, mkd. & witnessed as described by Asher Ireland, Assistant Forest Ranger. I mark the boulder 3 HES 93, with a cross (+) on top side, and S end, for Cor. 3, from which

A fir, 24" dia., bears S.15°15'E., 161 lks., blazed & scribed 3 HES 93 BT.

A basalt boulder, 3 ft. E & W, 2 ft N & S, 1 ft. high, mkd B R with cross (+) bears S.57°08'W., 32 lks.

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9728

-----

Cor. No. 3 HES No. 93, which is a cross (X) on S end of boulder in place, 4x4x½ ft. above ground, marked & witnessed as described in the official record.

Marvin C. Ramsey - For: J.H. Baxter & Co. - Witnesses: J. Goodin & R. Schultz - Sept. 12-22, 1960 - C.S. File 51/126

-----


A basalt boulder in place 5 ft. NE & SW, 3' NW & SE, flush with a fill. The reference points have been destroyed.

New BTs- 16" D.Fir bears S.2°E., 9 lks mkd 3 HES 93 RS404 BT.  
12" D.Fir bears N.13°E. 41 lks mkd 3 HES 93 RS404 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - Nov. 3, 1969 - C.S. File 52/43-33

-----

Found - Corner stone as called for, buried in old fill for driveway which is very seldom used. 1960 ren.  
16" now 17" D.Fir, alive, S.2°E., 5.9 ft. scribe, visible, we tag.  
12" now 14" D.Fir, alive, N.13°E., 27.1 ft. scribe, we tag.

Set - Brass cap at SW end of stone, flush with road surface  
mkd: COUNTY SURVEYORS OFFICE 1969 T26S R2E   
COR. #3 HES 93

The SE corner of cabin bears S.34½°W., 36.3 ft.

PRIMARY CORNER DESCRIPTION Cor. No. 3 HES 93

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Robert Dean, LS 1808 - For: USFS - Jan. 25, 1985 - M98-27 & C.S. File 63/5-3

-----  
Found - At corner location by NE BT per 1960 ren. I fd a 3' by 2' cinder stone, "H" visible, all other marks worn off by road travel, no marks at corner location, from which  
2½" brass cap, (properly) marked per 1969 ren., bears N.84°13'W., 1.60';  
18" D.Fir healed scar, bears N.13°00'E., 27.06' (rec. N.13°E., 27.06' per 1960 ren.)  
28" D.Fir, no marks, bears S.64°34'E., 26.9' (rec. 26.10' to face of 12" Fir per M14-5\*)  
24" D.Fir, no marks, bears N.73°53'W., 31.3' (rec. 30.95' to face of 8" Fir per M14-5\*)  
20" D.Fir, healed scar, bears S.2°45'W., 6.1' (rec. S.2°E., 5.94' per 1960 ren.)  
SE cor of cabin, bears N.35°50'W., 37.2' (rec. N.34½°W. 36.3' per 1969 ren.)

I add figures "→ RM LS1808" to cap.

\* no bearings given on M14-5 to tack on target on trees

Douglas Co. Surveyors Office - Stephen Flause - John Pike - 3/3/2006 - C.S. File 67/14-14

-----  
Found - 2½" dia., DCSO brass cap ref. mon. 3" below surface of gravel rd & at NW corner of large stone buried 6" deep We did not dig up stone used Dean's rec. of S.84°13'E., 1.60 ft. for stones position to tie in accessories.  
18" D.Fir now 25" dia., x 5 ft. tall sawed stump healed double blaze visible, bears N.13°E., 27.1 ft. (agrees w/rec) 1960  
28" D.Fir now 36" dia., x 3ft. tall sawed stump. No visible blazes bears S.64½°E., 26.9 ft. (Agrees w/rec M 98-27) 1959 (M 14-5)  
20" D.Fir now 24" dia., x 6 ft. tall sawed stump, healed double blaze visible bears S.2¾°W., 6.1 ft. (agree w/rec M 98-27) 1960 BT  
SE corner of 16'x22' shingle side cabin bears N.36°W., 37.2 ft. (agrees w/rec. M98-27)  
Large buried boulder is fd close to rec. brg. & dist. No clear markings fd. (Rec. S.57¼°W., 21.1 ft.) OBO 1914  
No trace of NW BT from M14-5

New - 24" dia., D.Fir, double blazed & scribed "3 HES 93 CS BT" bears S.41°W., 19.7 ft.

continued next page

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 993030

PRIMARY CORNER DESCRIPTION Cor. No. 3 HES 93

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

11" dia., W.Oak, double blazed & scribed "3 HES 93  
CS BT" bears N.55°E., 74.5 ft.  
1/2" I.D. iron pipe, buried 10" deep leans SW'ly  
bears N.87°W., 67.8 ft. (B&D meas. to top of  
IP) M14-5

Note - Corner lies on South edge of gravel Rd. that is soon  
to be decommissioned.  
Compass decl. 16¾ E.