

PRIMARY CORNER DESCRIPTION Cor. No. 4 HES 93

Alias	Description
Alias	Description
Alias	Description
Alias	Description

HES No. 93 by Frank D. Maxwell, Forest Service Surveyor, under special instructions dated July 7, 1913 - Surveyed July 1914 - DCSO records Vol. 28 Page(s) 12161

Cor. No. 4, identical with Cor. H/3 of listing survey, a post mkd. and witnessed as described by Asher Ireland, Assistant Forest Ranger, in place of which I set a basalt stone, 24x10x6", 14" in the ground, for Cor. 4, mkd. 4 HES 93 on NE face, with a cross on top, from which
 A fir, 30" dia., bears S.50°15'E., 72 lks.
 A fir, 15" dia., bears N.17°10'W., 89 lks.
Both trees blazed and scribed 4 HES 93 BT.

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9728

Cor. No. 4 HES No. 93, which is a stone, 6x6x10" above ground, in the official record.

R.R. Whitcher, Resident Eng'r, Bureau of Public Road, Dep't of Interior - 2/12/1959 - M14-5 - Note on map by Fred Darby, Douglas Co. Surveyor

Corner No.4, 2 Trees with Tack on Targets.
Distances given but no bearings.

Robert Dean, LS 1808 - For: USFS - Jan. 25, 1985 - M98-27 & C.S. File 63/5-3

At corner location by intersection of distances from BTs:
Set - A 3/4"x36" iron rod in north shoulder of highway, stamped "LS 1808" on top, from which:
 43" D.Fir, low healed scar, I open and find a burnt face 16" deep, I count 70 rings to face, bears N.16°05'W., 58.75 ft. (Rec. N.17°10'W., 58.74 per HES 93)
 18" D.Fir, no marks, I scribe "4 HES 93 BT", bears S.44°53'E., 121.98 ft. (Rec. per M14-5 S.44°54'E., 121.65 ft. to face of 8" fir.)
 11" D.Fir, no marks, stake and tack high facing corner, I scribe "X BT" bears S.41°45'W., 110.99 ft. (Rec. per M 14-5 110.74 ft. to face of 6" fir.)
 A 1/2" galv. I.P. bears N.9°26'W., 32.48 ft. (Rec. N.9°45'W., no distance per M14-5, N.9°45'W., 30.37 per M51-51)

continued next page

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 993040

PRIMARY CORNER DESCRIPTION Cor. No. 4 HES 93

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A ½" galv. I.P. no record, bears S.9°55'E., 64.51 ft
New BTs- A 22" D.Fir, scribed "4 HES 93 BT" bears N.59°20'W.,
129.8 ft.
A 17" D.Fir, scribed "4 HES 93 BT" bears S.36°30'W.,
91.4 ft.
New RM - A 2"x30" magnetic alum. monument, marked "LS 1808 RM
T26S R2E \HES 93 55 ft \ to cor 1985", in 36"
cairn, bears N.9°48'30"W., 55.00 ft.
I nail a 3/4" brass disc, stamped "RLS 1808", low to the face
of each new scribed BT.