

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 993050

PRIMARY CORNER DESCRIPTION Cor. No. 5 HES 93

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

HES No. 93 by Frank D. Maxwell, Forest Service Surveyor, under special instructions dated July 7, 1913 - Surveyed July 1914 - DCSO records Vol. 28 Page(s) 12161

Cor. No. 5, identical with Cor. H/4 of listing survey, 430 ft above point asc., a post mkd. and witnessed as described by Asher Ireland, Assistant Forest Ranger, in place of which, I set a basalt stone, 24x10x8", 14" in the ground, for cor. 5, mkd. 5 HES 93 on SE face, with cross (+) on top, from which
 A fir, 36" dia., bears N.66°30'E., 175 lks., blazed & scribed 5 HES 93 BT.
 No other trees within limits.
 I raise a mound of stone, 3 ft base, 2 ft high, SE of cor.

GL0 Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9728

Cor. No.5, HES No. 93, which is a stone, 8x8x8" above ground, firmly set, mkd & witnessed as described in the official rec.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 11/4/1969 - C.S. File 52/43-35

Found - Corner stone, in place, as called for, mkd: "5 HES 93 on side facing claim.
 Orig. 36", now 48" D.Fir, alive, N.66½°E., 115.5 ft. prev. opened with scribe marks visible.
Set - Brass cap at cor. in place of corner stone, Reset corner stone alongside.
 COUNTY SURVEYORS T26S R2E
 OFFICE 1969 COR. #5 HES 93
New BTs- 28" D.Fir N.69°W., 46.6 ft. mkd: "5 HES 93 CS BT"
 6" W.Oak S.26°W., 7.4 ft. mkd: "5 HES 93 CS BT"
This corner lies on very steep, SW slope about 100' W of top of spur, ridge sloping SE.

Robert Dean, LS 1808 - For: USFS - Jan. 25, 1985 - M98-27 & C.S. File 63/5-3

Found - 1" galv. iron pipe with 2½" brass cap per 1969 ren. 10"x16" stone marked "5HES93" lies north 0.5 ft.± 48" D.Fir, healed scar, bears N.66°00'E., 115.5 ft. (per HES 93 N.66°30'E., 115.5 ft)
 19" W.Oak, burnt & hollow opening faces corner bears S.24°50'E., 194.3 ft. (Rec. S.26°E., 193.4 ft. per listing survey)
continued next page

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 993050

PRIMARY CORNER DESCRIPTION Cor. No. 5 HFS 93

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

7" W.Oak, healed scar, bears S.25°00'W., 7.3 ft.
(Rec. S.26°W., 7.4 ft. per 1969 ren.)
34" D.Fir healed scar, bears N.69°10'W., 46.3 ft.
(Rec. N.69°W., 46.6 ft. per 1969 ren.)

FD BC by M. Heimbürger, 7/5/1994, PP 1994-0073 A&B
Fd. Ok by K. DeGroot, 9/1999, M133-29
Fd. BC by B Knapp, 3/2016 - 2021-0016A-B