

PRIMARY CORNER DESCRIPTION Cor. No. 6 HES 93

Alias	Description
Alias	Description
Alias	Description
Alias	Description

HES No. 93 by Frank D. Maxwell, Forest Service Surveyor, under special instructions dated July 7, 1913 - Surveyed July 1914 - DCSO records Vol. 28 Page(s) 12161-2)

Cor. 6, 175 ft. above creek, identical with Cor. H/5 of listing survey, a post, mkd. & witnessed as described by Asher Ireland, Assistant Forest Ranger; in place of which I set a basalt stone, 24x14x9" in the ground, for cor. 6 mkd. 6 HES 93 on SE with cross (+) on top, from which

A fir, 15" dia., S.54°15'W., 55 lks.
An Oak, 18" dia., bears N.61°20' W., 60 lks.

Both trees blazed & scribed 6 HES 93 BT.

GLO Survey by Otto S. Draper, U.S. Transitman, under Special Instructions dated Dec. 24, 1920, surveyed Sept. 1929/Aug. 1930 - (DCSO records Vol. 23 Page(s) 9728

Cor. No. 6 HES No. 93 which is a stone, 8x12x10" above ground, firmly set, marked & witnessed as described in the official record.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - 11/5/1969 - C.S. File 52/43-37

Found - Corner Stone, as called for, in place, Mxd: "X" on top & "6 HES 93" on side facing claim.
Orig. 18", now 22" Oak, alive, N.61°20'W. 49.5 ft. (Rec.39.6') Open & find "6" reverse scribe, blaze faces corner stone.
Orig. 15", now 24" Fir, now stump, S.54°15'W. 68.0 ft. (Rec. 36.3') Open & find "6HE" scribe & reverse, blaze face corner stone.

We assume orig. dist. to be in error & accept orig. bearings - In place of old cor. stone:

Set - Brass cap in place of old corner stone mkd:

COUNTY SURVEYORS	T26S R2E
OFFICE 1969	COR. #6 HES <u>93</u>

New BTs- 8" W.Oak N.36°W., 25.3 ft. mkd: "6 HES 93 CS BT"
12" Pine N.77°W., 33.0 ft. mkd: "6 HES 93 CS BT"

This corner lies on steep, SW slope.

Robert Dean, LS 1808 - For: USFS - Jan. 25, 1985 - M98-27 & C.S. File 63/5-3

Found - 1" galv. I.P. with 2½" brass cap per 1969 Ren. from which:

A 15"x7" stone, marked "+" bears North 0.5 ft. +.

continued next page

TOWNSHIP 26 RANGE 02E POINT IDENTIFIER # 993060

PRIMARY CORNER DESCRIPTION Cor. No. 6 HES 93

Alias	Description
Alias	Description
Alias	Description
Alias	Description

11" S.pine windfall, "6HES93CSBT" bears N.76°15'W., 32.5 ft. (Rec. N.77°W., 33.0 ft. per 1969 Ren.)
17" Oak snag, hollow axed opening faces corner bears N.61°20'W., 50.0 ft. (Rec. N.61°20'W., 39.60 ft. per HES 93, rec. N.63°W., 49.50 ft. per Listing Survey)
10" W.Oak, healed scar, bears N.35°50'W., 25.2 ft. (Rec. N.36°W. 25.3 ft. per 1969 Ren.)
26" D.Fir stump, "6H" visible at 5" center, bears S.54°30'W., 67.8 ft. (Rec. S.54°15'W., 36.30 ft. per HES 93)
New BT - 16" D. fir, scribed "6HES93BT" a 3/4" brass disc stamped "RLS 1808" is nailed low to the face, bears N.87°50'W., 47.3 ft.

Fd BC by Mark Heimburger, 7/5/1994, 1994-0073 A&B
Fd. OK by K DeGroot, 9/1999, M133-29