

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T26-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #56 dated March, 1855  
(DCSO Records, Volume 10 Page 4177)

-----  
Set post cor. to secs. 25, 36, 30 and 31, from which  
A Red Fir 26" dia., bears S.45°E., 33 lks. dist.  
A Red Fir 30" dia., bears N.22°E., 30 lks. dist.  
A Laurel 12" dia., bears S.68°W., 40 lks. dist.  
No trees convenient NW.

GL0 resurvey by Charles M. Collier, Under Special  
Instructions dated May, 1913. (DCSO records, Volume 10 Pages  
4255-56)

-----  
Cor. located by reference to the bearing trees as described  
by the surveyor general; all other traces of the cor. have  
disappeared. I re-establish this cor. in its original  
position, as follows:

Set a fir post, 3 ft. long, 4" sq. 24" in the ground, for  
cor. marked T26S S30 on NE., R2W S31 on SE., S36 on SW and  
R3W S25 on NW faces, with 1 notch on S and 5 notches on N  
edges, witnessed by the following bearing trees:

A Red Fir 30" dia., bears N.22°E., 30 lks. dist., marked  
T26S R2W S30 BT.

A Red Fir 26" dia., bears S.45°E., 33 lks. dist., marked  
T26S R2W S31 BT.

A Laurel 12" dia., bears S.68°W., 40 lks. dist., marked  
T26S R3W S36 BT.

Doug. County Surveyors Office - Vernon Tracy; Mike Stone;  
Jerry Layne - Jan. 1966 - C.S. File 54/7-31

-----  
Found - Orig. 26" D.Fir S.45°E., 21.8 ft. prev. opened &  
shows good "S" scribe.

No trace of SW ABT and NE BT could be rotted log  
laying in approx. location.

Set brass cap at cor. mkd: County Surveyors T26S

Office, 1966 R3W 

S 25	S 30
S 36	S 31

New BTs - 6" D.Fir N.61°E., 4.5 ft. mkd. T26S R2W S30 CS BT.

6" D.Fir N.5°W., 16.4 ft. mkd. T26S R3W S25 CS BT.

7" D.Fir S.37°W., 7.5 ft. mkd. T26S R3W S36 CS BT.

Corner found and used, BLM Dependent Resurvey, by Wayne  
Rogers, Group #1058 - June-Aug. 1981 (DCSO records, Vol. 45 Pg  
17436-37)

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T26-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ronald Geisler, for Champion International (Lynn Sibley; Dean Turner, field crew) June 30, 1987 - C.S. File 63/60-5

-----  
Found - 1966 County 2½" brass cap on a 1" iron pipe extends 12" above ground.  
9" D.Fir bears S.37°W., 7.5 ft. healed face.  
9" D.Fir bears N.5°W., 16.4 ft. healed face.  
36" D.Fir bears N.45°W., 21.8 ft. chopped face. bearing marks visible. (Orig. BT)  
8" D.Fir now down & uprooted bears N.61°E., 4.5 ft.  
New BT - 5" D.Fir bears N.74°E., 23.3 ft. scribed "T26S R2W S30 BT".

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Jeff Lorsung - 9/2/2020 - C.S. File 67/46-39

-----  
Found ok  
(1987) 36" D.Fir quad error (see 1913 GLO record) should be S.45°E.  
(1987) 5" D.Fir now dead 7"x12' snag - scribing visible.  
Found new BT (as of 12/2020 unrecorded 2019 BLM)  
10" Fir PHDB pitched over N.77°E., 37.7 ft.  
Lat: 43.271309937° Long: -122.990716377°

Dependent resurvey by Jeffrey O Covington, cadastral Surveyor under Group 2953, Surveyed Sept/Oct 2019 (DCSO Records Vol. 59 Pages 23986-23988 and Plat maps T26-3 2021-1 thru 2021-3)

-----  
The cor. of secs. 25, 30, 31, & 36, on the E bdy. of the Tp., reported by Rogers in 1981; and perpetuated by Geisler, in 1987, monumented with an iron post, 1¼" dia., firmly set, projecting 12" above ground, with a brass cap (properly) mkd. from which the remains of the BTs reported by Rogers  
A fir, 41" dia., bears S. 45°E., 21 8 ft., with a healed blaze. (Original)  
A fir, 13" dia., bears S.37½°W., 7.6 ft., with a healed blaze.  
A fir, 13" dia., bears N.7°W., 16.5 ft., with a healed blaze.  
and the remains of a BT mkd. by Geisler  
A fir snag, 5" dia., bears N.72°E., 23 3 ft., with scribe marks T26S R2W S30 visible on partially healed blaze.  
and a new bearing tree  
A fir, 12" dia., bears N.77°E., 37.7 ft., mkd. T26S R2W S30 BT.

Lat: 43°16'16.71"N Long: 122°59'26.49"W NAD 1983 (2011)  
continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 100200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 30 & 31; 25 & 36, T26-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.

Lat: 43°16'16.71"N Long: 122°59'26.49"W NAD 1983 (2011)

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorusung- 5/19/2021 (Filed 11/22/2021) - C.S. File 67/51-5

-----  
Found - 2½" brass cap on 1" iron pipe projects 12" above ground.  
1913 BT, 36" D.Fir S.45°E., 21.8 ft., chopped face, visible scribe.  
9" D.Fir S.37°W., 7.5 ft., good scar.  
9" D.Fir N.5°W., 16.4 ft., good scar.  
New - 10" Fir N.77°E., 37.7 ft., partly healed double blaze. (Un filed BLM Survey \*see above 3/15/2022)

Note - Compass decl. 14½°E.

Lat: 43.271309937° N Long: 122.990716377° W  
43°16'16.75" N 122°59'26.48" W