

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24, 25, T26-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 10 Page 4177)

Set post cor., from which

- A Laurel 5" dia., bears N.2°E., 27 lks. dist.
- A Laurel 6" dia., bears N.55°W., 32 lks. dist.
- A R.Fir 4" dia., bears S.88°E., 17 lks. dist.
- A R.Fir 4" dia., bears S.48°W., 35 lks. dist.

Corner referred to by Samuel Flint, GLO Surveyor, in June,
1882 (DCSO records, Volume 10 Page 4387)

GLO survey by William N. Gibb, Under Contract #783 dated
December 3, 1908 (DCSO records, Volume 10 Page 4247-48)

Found a stake which is greatly decayed, marked as described
Surveyor General. Bearing trees have been destroyed.
Set granite stone, 8x10x14 ins., 10" in the ground for cor.,
marked with 4 notches on N and 2 notches on S edge, from
which

- A Fir 8" dia, bears N.52°E., 27 lks. dist., marked
T26S R2W S19 BT.
- A Fir 8" dia., bears S.14°E., 26 lks. dist., marked
T26S R2W S30 BT.
- A Laurel 6" dia., bears S.10°W., 16 lks. dist., marked
T26S R3W S25 BT.
- A Fir 6" dia., bears N.18°W., 18 lks. dist., marked
T26S R3W S24 BT.

Lester E. Calder, For: Weyerhaeuser Company, October 1, 1952
C.S. File 41/76

Found - A stone with 4 notches on the North and 2 notches
on

- South ends and 3 original BTs.
- 14" Fir N.20°W., 11.8 ft. (Orig. BT.)
- 18" Fir N.55°E., 16.7 ft. (Orig. BT.)
- 16" Fir S.16°E., 16.9 ft. (Orig. BT.)
- 16" Fir S.56°W., 17.6 ft.

Doug. County Surveyors Office - Karen Reed; P.L. Earle - May
9, 1979 - C.S. File 60/24-30

Found - 8x10x14" granite stone, 4 notches on north, 2
notches on south, lying on top of ground.
(Rec. buried 10" below ground) (1902 resurvey)
No trace of original BTs. continued next page

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

8" Fir now 22" bears N.58°E., 17.5 ft. (Rec. N.52°E., 17.8 ft., 1902; N.55°E., 16.7 ft. to face per Caldwell, 1952.) with well healed blaze.

8" Fir now 18" bears S.14°E., 17.6 ft. with healed blaze (Rec. S.16°E., 16.9 ft.) to face.

6" Fir now 15" bears N.25°W., 12.4 ft. visible scribing in chopped out blaze "S24 BT" (Rec. N.18°W., 11.9 ft., 1902; N.20°W., 11.8 ft. to face per 1952 visit.)

16" Fir bears S.51°W., 18.3 ft. with healed blaze. (Rec. S.56°W., 17.6 ft. to face)

Set - 1" x 36" I.P. with brass cap mkd. "Douglas County Surveyor"
T 26 S
R S 24 | S 19 R
3 S 25 | S 30 2
W 1979 W

Note: Bearings and distances did not hit one spot - Placed cap at appropriate distance securing a bearing to the 18" Fir, S.14°E.

BLM rehabilitation of certain corners, Timothy J. Moore, Cadastral Surveyor & Robert H. Browning, Surveying Tech., under Group #2100, & 2300, Surveyed April/May 2004, - (DCSO records Vol. 55 Page(s) 21499) See 2008 BLM plat.

The cor. of secs. 19, 24, 25, & 30 on the E bdy of the Tp, perpetuated by Calder in 1952 & remonumented by the Douglas Co. Surveyors office in 1979, monumented with an iron post 1¼" dia., firmly set (properly mkd), projecting 6" above ground (the orig. stone 8x10x14" buried alongside, projecting 2" above ground, with no marks visible) from which the remaining BTs mkd by Gibb

A fir, 25" dia. bears N.52°E., 17.8 ft with healed blaze

A fir, 21" dia. bears S.14°E., 17.2 ft with healed blaze

A fir, 16" dia. bears N.18°W., 11.9 ft with healed blaze

and BT mkd by Calder

A fir, 16" dia. bears S.51¼°W. 17.8 ft with healed blaze

NAD 1983 (CORS)

Latitude 43°17'08.77"N

Longitude 122°59'28.04"W

Fd as per 2004 BLM resurvey by D. Edwards, 10/2012 - M164-32

continued next page

2

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; 24, 25 T26-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2817, surveyed Oct./Nov. 2015 - (DCSO records Vol. 58 Page(s) 23487 & Plat T26-2 2017-1)

The cor. of secs. 19, 24, 25, & 30, on the W. bdy. of the Tp., monumented with an iron post, 1¼" dia., firmly set, projecting 8" above the ground, (the original stone, 8x10x14", buried alongside, projecting 2" above the ground, with 4 grooves visible on N. face and 2 grooves visible on S. face) with brass cap (properly) mkd.

from which the remaining BTs mkd. by Gibb in 1909-10, and reported by Moore in 2004

A fir, 27" dia., bears N.52°E., 17.8 ft., with a healed blaze.

A fir, 32" dia., bears S.14°E., 17.2 ft., with a healed blaze.

A fir, 18" dia., bears N.18°W., 11.9 ft., with a healed blaze.

and a BT mkd. by Calder, in 1952, and reported by Moore

A fir, 17" dia., bears S.51½°W., 17.8 ft., with a healed blaze.

A steel fence post is alongside the cor.

NAD 1983 (2011)

Latitude 43°17'08.77"N.

Longitude 122°59'28.04"W