

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 18; & S.13 of T26-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 10 Page 4178)

Set 1/4 post on side hill, from which
 A R. Fir 96" dia., bears S.20°W., 22 lks. dist.
 A Hemlock 10" dia., bears S.47°E., 12 lks. dist.

GLO survey by Charles M. Collier, Under Instructions dated
May 12, 1913 (DCSO records, Volume 10 Page 4251)

Cor. located by reference to the SW bearing tree which is a
red fir, marked as described by the surveyor general; all
other traces of the cor. have been obliterated. I reestablish
this cor. in its original position, as follows:

Set a basalt stone 12x8x6" 8" in the ground, for 1/4 sec. cor.
marked 1/4 on W. face; from which
 A Red Fir 96" dia., bears S.20°W., 22 lks. dist., marked
 1/4 S B T. (Original BT)

Doug. County Surveyors Office - Vernon Tracy; Glen McChesney,
Weyerhaeuser Co. witness; M. Darby and Terry Connell
June 1965 - C.S. File 54/7-33

Found - Orig. 96" now 96" Fir stub S.20°W., 14.5 ft. shows
old axe blaze with partial "S" scribe in bark.
Find very old blazes on trees both N & S of corner.
No rock found.

Set brass cap at cor. mkd: County Surveyors Office, 1965
T 26 S R3W 1/4 S13|S18 R2W

New BTs - 10" Hemlock S.32°W., 9.3 ft. mkd. 1/4 S13 CS BT.
7" Hemlock N.27°E., 18.9 ft. mkd. 1/4 S18 CS BT.

Donald Peel, for: Weyerhaeuser - Nov. 1974 - M 54-76

Found - 1965 DCSO brass cap.
6" Cedar stub N.27°E., 18.9 ft.
10" Hemlock snag S.34°W., 9.4 ft.
New BTs - 8" Cedar S.85°E., 23.5 ft.
16" Cedar S.65°W., 57.3 ft. (dist. to form nail at
base of tree)