

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12 of T26-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855  
(DCSO Records, Volume 10 Page 4179)

-----  
Set post cor. to secs. 1, 12, 6 and 7, from which  
A Cedar 8" dia., bears S.60°E., 15 lks. dist.  
A Cedar 15" dia., bears S.60°W., 30 lks. dist.  
A Cedar 13" dia., bears N.68°E., 30 lks. dist.  
A R.Fir 16" dia., bears N.46°W., 88 lks. dist.

-----  
GLO survey by W.H. Byars, Contract #317, Jan. 20, 1879  
(DCSO records, Vol. 10 Page 4381)

-----  
Said post was found rotted down., witness trees all standing:  
A Cedar 20" dia., bears N.68°E., 30 lks. dist.  
A Cedar 16" dia., bears S.60°E., 15 lks. dist.  
A Cedar 24" dia., bears S.60°W., 30 lks. dist.  
A Red Fir 20" dia., bears N.46°W., 88 lks. dist.  
Trees same as notes furnished except their growth.  
Set new cedar post, 36" long, 10" wide, 4" thick, 20" in  
ground.

-----  
GLO resurvey by Charles M. Collier, Under Instructions dated  
May 12, 1913 (DCSO records, Volume 10 Page 4253)

-----  
Point for corner located by reference to the bearing trees as  
described by the surveyor general; all traces of corner have  
disappeared. I re-establish this cor in its original position  
as follows:  
Set a basalt stone, 14x7x7 ins., 9" in the ground, marked with  
5 notches on S. and 1 notch on N. edge; witnessed by the orig.  
bearing trees as follows:  
A Cedar 13" dia., bears N.68°00'E., 30 lks. dist.,  
marked T26S R2W S6 BT.  
A Cedar 8" dia., bears S.60°E., 15 lks. dist., marked  
T26S R2W S7 BT.  
A Cedar 15" dia., bears S.60°W., 30 lks. dist., marked  
T26S R3W S12 BT.  
A Red Fir 16" dia., bears N.46°W., 88 lks. dist., marked  
T26S R3W S1 BT.

-----  
BLM resurvey by Zirpel & Glenn, May/Oct. 1959 under Special  
Instructions dated Nov. 1958, Group #404 (DCSO records,  
Volume 30 Page 12724)

-----  
(Cont. Next Page)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7; 1 & 12 of T. 26-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Found the cor. perpetuated with an iron pipe 2" dia., protruding 36" above ground, firmly set, at record bearing and distance from each or the two remaining original bearing trees:

A Cedar 36" dia., bears S.60°W., 30 lks. dist., with a healed blaze.

A Fir 30" dia., bears N.46°W., 88 lks. dist., with scribe marks T26S R3W S1 visible on a partially opened blaze.

and locally established bearing trees

A Hemlock 10" dia., bears N.37°E., 17½ lks. dist., mkd. with a partially healed blaze and a nail stamped W on head. Re-mark this tree T26S R2W S6 BT.

A Cedar 12" dia., bears S.73°E., 41 lks. dist., mkd. with a nail stamped W on head. Re-mark this tree T26S R2W S7 BT.

At corner point, set an iron post, 28" long, 2½" dia., 24 ins. in the ground, with brass cap mkd:

T	26	S
R	3	W
R	2	W
S	1	S
S	12	S
		6
		7
		1959

Deposit the iron pipe alongside the iron post.

BLM resurvey by White; Beck and Reynolds, June 1962 to Aug. 1963 Under special instructions dated Aug. 1963 under Group No. 491; 242;527. (DCSO records, Volume 32 13372)

-----  
Found 1959 brass cap protruding 7" above ground, from which the remaining original bearing trees

A Fir stump 30" dia., bears N.46°W., 88 lks. dist., with scribe marks T26S R3W S1 visible on partially opened blaze.

and 1959 bearing tree

A Hemlock 10" dia., bears N.37°E., 17½ lks. dist., mkd. T26S R2W S6 BT.

A Cedar 12" dia., bears S.73°E., 41 lks. dist., mkd. T26S R2W S7 BT.

add one new bearing tree

A Fir 35" dia., bears S.66°W., 123 lks. dist., marked T26S R3W S12 BT.

(Cont. Next Page)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. 6 & 7; 1 & 12 of T.26-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Doug. County Surveyors Office - R.B.Kimberling; P.L.Earle;  
S.J. Flause - Jan. 10, 1978 - C.S. File 59/46-14

-----  
Found - 1959 Cadastral brass cap on a 2½" I.P. 7" above  
ground properly marked.  
15" now 36" Cedar stump is pushed over. Orig.  
position bears approx. S.60°W., 19.8 ft. but no  
visible blaze. (OBT)  
Remains of a Fir stump bears N.46°W., 58.1 ft. (OBT)  
12" now 13" Cedar snag bears S.73°E., 27.1 ft. with  
scribing "T26S R2W S7 BT" in single blaze.  
(1959 resurvey)  
50" Fir stump with a Weyerhaeuser tag and blaze  
bears S.60°W., 35.0 ft.  
28" Fir stump with a Weyerhaeuser tag and blaze  
bears N.59°W., 47.4 ft.  
New BTs - 13" Cedar with "MR" carved in West face bears  
N.83°E., 20.0 ft. double blazed and scribed  
"T26S R2W S6 CS BT"  
10" D.Fir bears S.20½°E., 124.1 ft. double blazed  
& scribed "T26S R2W S7 CS BT".  
3" "X" chiseled 3 ft. above ground in a 20 ft. x 20  
ft. boulder bears S.88½°W., 32.0 ft.  
6" Chinquapin bears N.50°W., 71.8 ft. double blazed  
and scribed "T26S R3W S1 CS BT".  
Corner is 30 ft. north of road.

See C.S. File 53/114-3 for Weyerhaeuser 1969 corner report.  
Added two new references, described in above DCSO corner  
visit.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike  
- 11/8/2007 - C.S. File 67/24-46

-----  
Fd. Ok, as per 1978 renewal.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral  
Surveyor, under Group No. 2923, surveyed July 2018/March 2020-  
(DCSO records Vol. 59 Pages 24046-7)

-----  
The cor. of secs. 1, 6, 7, & 12, reported by White, Beck, and  
Reynolds in 1962-63; perpetuated by the Douglas County  
Surveyor's Office in 1978; monumented with an iron post, 2½"  
dia., firmly set, projecting 8" above ground, (alongside of  
which is an iron pipe, 2" dia., firmly set, projecting 30"  
above ground) with a brass cap (properly) mkd. Cont.

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. 6 & 7; 1 & 12 of T.26-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of a bearing tree mkd. by person(s) unknown, reported by the Douglas County Surveyor's Office  
A decayed fir stump, 24" dia., bears N.61¼°W., 47.4 ft., no marks visible.  
and the accessories established by the Douglas County Surveyor's Office  
A cedar, 27" dia., bears N.81¼°E., 19.6 ft., with a healed blaze.  
A fir, 20" dia., bears S.23¾°E., 127.0 ft., with a healed blaze.  
A boulder, 20x20x4 ft. high, bears S.86½°W., 32.1 ft., with a chiseled X on the E. face.  
A tan oak, 9" dia., bears N.52¼°W., 71.8 ft., with a healed double blaze.  
Corner is located N., 65 ft., of a graveled road, 20 ft. wide, bears S.55°E. and N.60°W.  
NAD 1983 (2011)  
Latitude: 43°19'44.75" N. Longitude: 122°59'28.27"W.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 9/16/2022 - C.S. File 67/54-18  
-----  
Found - 3¼" BLM brass cap on 2½" I.Pipe, up 8" - 2" I.Pipe on WNW edge of brass cap, up 30"  
Burnt-dead 28" Cedar N.83°E., 20.0 ft., burnt out face. 1978  
A 3"x3' above ground in 20x20' boulder S.86°W., (rec. S.88½°W.) 32.0 ft.  
8"x7' sawn chinquapin stump N.53°W., (rec. N.50°W.) 71.8 ft., healed double blaze.  
New - 5/8"x30" I.Rod with DCS0 yellow plastic cap, S.5°W., 63.4 ft in fill slope of road shoulder, projecting 3".  
Note - Corner is 30±" of road.  
Compass decl. 14½°E.  
See sketch in file.  
OCRS state plane co-ordinates  
Cottage Grove - Canyonville Zone (SEE 2018/2020 BLM Report for Lat/long)  
N 180887.011 E 255081.218