

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6; & S 1 of T. 26-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #56 dated March, 1855  
(DCSO Records, Volume 10 Page 4179)

-----  
Set ¼ sec. post, from which  
A R. Fir 60" dia., bears S.50°W., 15 lks.  
A R. Fir 18" dia., bears S.88°E., 22 lks.

GL0 survey by Charles M. Collier, under instructions dated  
May 1913 (DCSO records, Volume 10 Pages 4253-54)

-----  
Cor. located by reference to the SE bearing tree as described  
by the surveyor general; the SW BT is fallen & decayed; all  
traces of the cor. have disappeared. I reestablish it in its  
original position, as follows:  
Set a fir post, 3 ft. long, 3" sq., 24" in the ground, mkd.  
¼ S 1 on W face & 6 on E face, witnessed by the orig BT as  
follows:  
A Red Fir 24" dia., bears S.88°E., 22 lks., mkd. ¼ S B T.

A. Boyer; B.A. Lane; Welden Stone; Maurice Reid - For: State  
Game Commission - May 22, 1937 - C.S. File 30/21A

-----  
Found original 24" Fir.  
New BT - 40" Fir, North 24.3 ft. mkd. ¼ S C.S. BT.

BLM resurvey by White; Beck & Reynolds, Under Special  
instructions dated April, 1940, Oct. 1962 and Aug.  
1963, Group #'s 242, 491, 527 (DCSO records, Volume 32 pgs.  
13372-73)

-----  
The ¼ cor. determined at record bearing and distance from one  
bearing tree marked by Collier in 1913:

A Fir snag 40" dia., bears S.88°E., 22 lks. dist.,  
with scribe marks BT visible on bark blaze.

and a local bearing tree

A Fir 50" dia., bears N.2°W., 47 lks. dist., mkd. ¼  
S1 CS BT on bark blaze.

Set an iron post, 28" long, 2½" dia., 12" in the ground,  
supported in a mound of stone, 3 ft. base, to top, with  
brass cap marked ¼

S 1 | S 6  
R 3 | W | R 2 W  
R 26 S  
1963

from which a new bearing tree

A Cedar 18" dia., bears S.53½°E., 41 lks., mkd. ¼ S6 BT.  
Corner falls on top of a ridge, bears NE. and SW.

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6; & S 1 of T. 26-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Doug. County Surveyors Office - V. Tracy and crew - Aug. 11, 1967 - C.S. File 54/40-56

-----  
Found - 1963 Cadastral brass cap set in mound of stone.  
Orig. 40" Fir now sawed stump, S.88°E., 14.5 ft. shows bark scribe.  
50" Fir N.2°W., 31.0 ft., alive, shows bark scribe in poor condition.  
18" Cedar S.53½°E., 27.1 ft. (1963 BT)  
New BT - 9" Hemlock N.53°W., 29.3 ft. mkd. ¼ S1 CS BT.  
This corner lies on top of ridge course NE and SW. at NE corner of cut-off unit.

Kevin Schinnell - For: Rosboro Lumber Co. - 1/2006 - M 149-35

-----  
Found - 3¼" brass monument on 3" iron pipe & accessories as follows:  
24" cedar S.55°E., 26.22'  
14" hemlock N.48°W., 29.72'  
56" fir N.02°E., 28.44'  
New - 20" hemlock S.82°W., 7.35'  
Note - All accessories repainted and flagged at this time.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 11/28/2007 - C.S. File 67/24-47

-----  
Found ok as noted:  
24" cedar - ok  
14" hemlock - ok  
56" Fir, now low stump  
20" hemlock S.82°W., 7.35' is not scribed, there is a low notch with nail & dist. 7.35 ft. is measured from nail to BC (face meas.)

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24048)

-----  
The ¼ sec. cor. of secs. 1 and 6, reported by White, Beck, and Reynolds, in 1962-63; perpetuated by the Douglas County Surveyor's Office, in 1967; subsequently perpetuated by Schinnell, in 2006; monumented with an iron post, 2½" dia., firmly set, projecting 15" above ground, in a mound of stone, 3 ft. base, 12" high, with a brass cap (properly) mkd from which the remains of the bearing trees reported by White, Beck, and Reynolds  
A decayed fir stump, 28" dia., bears S.88°E., 14.5 ft., with a portion of the healed blaze intact. (Orig)cont

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 100640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6; & S. 1 of T. 26-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A cedar, 31" dia., bears S.53½°E., 27.1 ft., with a healed double blaze.  
A fir stump, 57" dia., bears N.2°W., 31.0 ft., no marks visible.  
and a bearing tree mkd. by the Douglas Co Surveyor's Office  
A hemlock, 16" dia., bears N.51½°W., 30.2 ft., with no marks visible on partially healed double blaze.  
and a bearing tree mkd. by Schinnell  
A hemlock, 25" dia., bears S.78°W., 9.0 ft., with axe marks visible on bark.  
Corner is located on top of a ridge, bears N.80°E. & S.75°W.