

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4247)  
-----  
Set a granite stone 6x9x14" 10" in the ground for 1/4 sec. cor. marked 1/4 on N face, from which  
A cedar, 18" dia., bears S.63°W., 16 lks., mkd: 1/4 S30 BT.  
A hemlock, 8" dia., bears N.40°E., 11 lks., mkd: 1/4 S19 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - July 1967 - C.S. File 54/40-19  
-----  
Found - Orig. corner stone 6x9x12" mkd. "1/4" on N face & firmly set.  
A large stump hole bears S.63°W., 10.0 ft. & a small stump hole bears N.40°E., 7.0 ft. These holes fit location for orig. BTs.  
Find OBT as follows:  
10" Laurel S.15°W., 20.9 ft. approx. ring count indicates this tree mkd. 50-55 yrs ago scribed "1/4 S30 BT".  
Pacing from top of ridge to East, this corner fits call good, old blazes found west.  
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T26S R2W  
OFFICE 1/4 S 19  
1967 S 30  
10" Cedar N.52°W., 10.9 ft. mkd: 1/4 S19 CS BT.  
10" D.Fir S.38°W., 16.6 ft. mkd: 1/4 S30 CS BT.  
Note - This corner lies on top of small rounding spur sloping N. Reset stone alongside Brass cap.  
Also find 9" Laurel snag, open & find "S19B" scribe & reverse bears N.89°E., 19.1 ft.

Douglas Co. Surveyors Office - Gary E. Commons - Pete L. Earle - Feb. 25, 1975 - C.S. File 57/17-21  
-----  
Found - 1967 County Surveyors Brass cap properly mkd.  
An orig. corner stone 6"x9"x12" with 1/4 on North face along side.  
A 9" Madrone snag N.89°E., 19.1 ft. is now down and apparently rotted.  
A 10" Madrone now 11" S.15°W., 20.9 ft. with scribing 1/4 S30 CS BT visible.  
A 10" Cedar, now 11", N.52°W., 10.9 ft. with scribing 1/4 S19 CS BT visible.  
A 10" D.Fir, now 11", S.38°W., 16.6 ft. is blown down, scribing visible.  
New BT - A 12" D.Fir, S.30°E., 23.0 ft. scribed 1/4 S30 CS BT.  
continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Note - Corner lies on top of ridge south easterly of old clearcut head of stream

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22936)

-----  
The ¼ sec. cor. of secs. 19 and 30, perpetuated by the Douglas County Surveyor's Office in 1967 and 1975, monumented with an iron post, 1¼" dia., firmly set, flush with ground surface, (buried alongside of which I unearth and rebury the original basalt stone, 6x9x14", with marks ¼ visible) with brass cap (properly) mkd.

from which bearing trees mkd. by person(s) unknown, recorded by the Douglas County Surveyor's Office in 1967

A madrone, 13" dia. bears S.10¾°W., 21.0 ft w/scribe marks ¼ S30 visible on a weathered, partially healed blaze. and the remains of BTs mkd. by the Douglas Co Surveyor's Office in 1967

A roothole, bears S.40½°W., 16.3 ft., with a partially uprooted, sawed, decayed, fir stump alongside, size indeterminate, with no marks visible.

A cedar, 22" dia., bears N.51½°W., 11.1 ft., with a healed blaze.

and the remains of a BT mkd. by the Douglas Co Surveyor's Office in 1975

A roothole, bears S.31¾°W., 24.1 ft., with an uprooted, decayed fir lying alongside, 12" dia., with no marks visible.

Douglas Co. Surveyors Office - Crew: Stephen Flauser & Jeff Lorsung- 1/11/2023 - C.S. File 67/55-22

-----  
Found - DCSO brass cap (properly mkd) on 1¼" Iron pipe set flush. Orig. Stone on N edge of BC.  
12"x2½' Madrone stump S.10¾°W., 21.0 ft., burnt out.  
A singed 22" Cedar N.51¼°W., 10.3 (Rec. 11.1) healed blaze add 3½" mag nail right side center.

New - 30" S.Pine N.53°E., 5.0 ft. 3½" mag nail right side center.

31" D.Fir S.78°W., 31.5 ft. 3½" mag nail right side center.

Aluminum Lath 0.5 ft. ENE

Note - Monument is at top of steep NW slope on a ENE running ridge 100± N of gravel road.

Area burnt 9/2020

Compass decl. 14½°E

Lat: 43°17'09.23" N Long: 122°58'51.00"W \_\_\_\_\_

