

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec 18 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GL0 survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4217)</p> <p>-----</p> <p>Set post, 3 ft. long, & 3" sq., 24" in the ground for the 1/4 sec. cor. marked 1/4 S on N face, from which:</p> <p> A fir, 8" dia., bears N.10°W., 43 lks., mkd: 1/4 S BT.</p> <p> A fir, 6" dia., bears S.21°W., 15 lks., mkd: 1/4 S BT.</p>
<p>GL0 survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4249)</p> <p>-----</p> <p>Unable to find any trace of 1/4 sec. cor. after diligent search Set a granite stone 7x8x15" 10" in the ground for 1/4 sec. cor. marked 1/4 on N face, and raise mound for stone, 2 ft. base, 1 1/2 ft. high N of cor. from which</p> <p> A laurel, 5" dia., bears N.85°E., 29 lks., mkd: 1/4 S18 BT.</p>
<p>GL0 resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4319)</p> <p>-----</p> <p>Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 cor. of sec. 18 only, with brass cap marked</p> <p style="text-align: center;"><u>1/4S18</u> <u>1918</u></p> <p>from which,</p> <p> A fir, 36" dia., bears N.47°E., 17 lks. mkd 1/4 S18 BT</p> <p> A fir, 18" dia., bears N.20°W., 58 lks. mkd 1/4 S18 BT</p> <p>From this cor. the cor established by Deputy Gibb as the 1/4 sec. cor. on S bdy. of sec. 18, bears S.44°04'E., 15.10 chs. I destroy the corresponding cor. which I established in 1916; also marks on BTs.</p>
<p>Frank Williams, WEYCO - By Glen McChesney - 1/29/1976 (added 8/9/2016) - C.S. File 59/46-12</p> <p>-----</p> <p>Found - 1918 brass cap</p> <p> 30" Fir, bears N.49°E., 10.8 ft. (rec. N.47°E., 11.2 ft.) rotted face.</p> <p> 22" Fir, bears N.19°W., 38.3 ft. (rec. N.20°W.) face healed over, "W" nail at base of tree.</p> <p>New - 44" Fir, bears S.33°W., 26.1 ft. with "W" nail & plate.</p>
<p>continued next page</p>

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec 18 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas Co. Surveyors Office - Gary Langlitz - Stephen Flause
- March 4, 1978 - C.S. File 59/46-11

-
- Found - A 1" I.P. extending 14" above ground on a steep easterly slope, with a 1918 GLO brass cap.
 - An orig. 36" D.Fir now 32" alive, but in poor condition, no scribing visible on rotten face, bears N.47°E., 11.2 ft.
 - An orig. 18" D.Fir now a 25" stump with well healed blaze bears N.20°W., 38.3 ft. "W-Nail" in base of this BT bears N.20°W., 37.0 ft (1918 resurvey)
 - Set - A "W-Nail" in the base of a 44" D.Fir bears S.33°W. 25.7 ft
At the present position of the 1918 GLO monument, we lower said monument to extend approx 3 inches above ground.
 - New - An 18" D.Fir scribed "RP S ¼ S18 CS BT" on a double blaze, bears S.77°E., 40.3 ft.
 - Note - Corner located along southerly edge of recently logged area.

BLM dependent resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2817, surveyed Oct./Nov. 2015 - (DCSO records Vol. 58 Page(s) 23487 & Plat T26-2 2017-1)

The ¼ sec. cor. of sec. 18 only, perpetuated by the Douglas County Surveyor's Office in March of 1978, monumented with an iron pipe, 1" dia., firmly set, projecting 2" above the ground, with brass cap (properly) mkd.
from which the remains of the BTs mkd. by Mensch in 1916-18

- A burnt fir snag, size indeterminate, bears N.47°E., 11.2 ft., with illegible scribe marks visible on an open blaze.
- A burnt fir stump, size indeterminate, bears N.20°W., 38.3 ft., with no marks visible and a spike in the stump facing the cor.

and the remains of a BT mkd. by persons unknown, reported by the Douglas County Surveyor's Office

- A burnt fir snag, 53" dia., bears S.29°W., 27.6 ft., with a healed blaze.

and the remains of a BT mkd by the Douglas Co. Surveyor's Office

- A burnt fir snag, 33" dia., bears S.77½°E., 41.3 ft., with a healed blaze.

and new reference monuments

- A stainless steel post, 28" long, 2½" dia., set 26" in the ground for a reference monument, bears S.47°32'43"W., 53.20 ft., with brass cap mkd. RM2 S19 53.2 FT TO COR 2015 and an arrow pointing to the cor. Build mound of stone, 2 ft. base, 1 ft. high, and drive an alum angle iron, 5 ft. long, alongside the stainless steel post. continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Sec 18 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A stainless steel post, 28" long, 2½" dia., set 26" in the ground for a reference monument, bears N.16°32'50" W., 26.20 ft., with brass cap mkd. RM1 ¼ S18 26.2 FT TO COR 2015 and an arrow pointing to the cor.
Drive an aluminum angle iron, 5 ft. long, alongside the cor.
Note: The source document for the perpetuation of this cor. by the Douglas County Surveyor's Office is CS 59/46. This document could not be found in the County Surveyor's Office at the time of this survey. The Douglas County Surveyor's Office Corner Renewal Index 140400 was utilized for the information for this cor. (Added 9/26/2017 See C.S. 59/46-11)

Douglas Co. Surveyor's Office - Crew: Jeff Lorsung - 10/28/2025 - C.S. File 67/61-36

Found - GLO brass cap on iron pipe proj 2".
23" x 20 ft. fir snag N.47°E. 11.4 ft. Add 3½" mag nail right side center.
Burnt 49" fir snag S.29°W. 27.8 ft. healed blaze. Add 3½" mag nail right side center.
Burnt 28" fir snag S.77½°E. 41.3 ft. healed blaze. Add 3½" mag nail right side center.
BLM brass cap reference monument S.47°32'43"W. 53.20 ft. stamped RM2 S19 53.2 ft. to corner. 2015 arrow pointing to corner.
BLM brass cap reference monument N.16°32'50"W. 26.20 ft. stamped RM 1 ¼ S18 26.2 ft. to corner 2015 arrow pointing to corner.
Alum. Angle iron 0.6 ft. east of monument.
Notes - Mon. on steep, rocky, east slope. Burnt and clear-cut. Approx. 270 ft. of access road.
Area burnt 9/2020.
Compass decl. 14¼°E.
O CRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
Lat. 43°17'57.084" N. Long. 122°58'53.364 W.