

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Pg 4219)

Set post, 3 ft. long, & 3" sq., 24" in the ground for the 1/4 sec. cor. marked 1/4 S, from which:

- A chinquapin, 8" dia., bears N.25°W., 38 lks., mkd: 1/4 S BT
- A hemlock, 6" dia., bears S.10°W., 22 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12748)

Point for the 1/4 sec. cor. of secs. 7 & 18, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 1/2" dia., 26" in the ground with brass cap marked:

T26S R2W
 1/4 S 7
 S 18
 1959

from which

- A fir, 18" dia., bears N.15°W., 58 lks., mkd: 1/4 S7 BT.
- A fir, 28" dia., bears S.19°W., 69 lks., mkd: 1/4 S18 BT.

Nick Juliano - For: Weyerhaeuser Co. - 9/1973 - C.S. 55/316-1

- Found - BLM pipe with brass cap
 24" cedar. S.17°W., 14.5', W.CO. tag.
 28" fir S.19°W., 69 lks. BT
 24" Fir, N.16°W., 37.3' BT

BLM dependent resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2817, surveyed Oct./Nov. 2015 - (DCSO records Vol. 58 Page(s) 23487 & Plat T26-2 2017-1)

The 1/4 sec. cor. of secs. 7 & 18, monumented with an iron post, 2 1/2" dia., firmly set, projecting 12", above the ground, in a mound of stone, 3 ft. base, to the top, with brass cap (properly) mkd.

from which the remains of the BTs mkd by Zirpel & Glenn in 1959

- A burnt fir stump, size indeterminate, bears S.19°W., 45.5 ft., with no marks visible.
- A burnt fir snag, 33" dia., bears N.15°W., 38.3 ft., with a healed blaze.

and new reference monuments

- A stainless steel post, 28" long, 2 1/2" dia., set 24", in the ground, in a collar of stone, for a reference monument, bears S.42°41'14"W., 19.50 ft., with brass cap mkd. RM1 1/4 S18 19.5 FT TO COR 2015 and an arrow pointing to the cor.

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A stainless steel post, 28" long, 2½" dia., set 24", in the ground, in a collar of stone, for a reference monument, bears N.45°16'47"W., 19.60 ft., with brass cap mkd. RM2 ¼ S7 19.6 FT TO COR 2015 and an arrow pointing to the cor.
Drive an aluminum angle iron, 5 ft. long, alongside the cor.