

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4222)

Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on N face, from which:
 A fir, 12" dia., bears S.55°E., 8 lks., mkd: ¼ S BT.
 A fir, 16" dia., bears N.60°W., 24 lks., mkd: ¼ S BT.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12751)

Point for the ¼ sec. cor. of secs. 6 & 7, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 25" in the ground with brass cap marked:

T26S R2W
 ¼ S 6
 S 7
 1959

from which
 A fir, 28" dia., bears N.57°W., 34 lks., mkd: ¼ S6 BT.
 A fir, 30" dia., bears S.11½°E., 33 lks., mkd: ¼ S7 BT.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24063-4)

The ¼ sec. cor. of secs. 6 and 7, reported by Zirpel, Jr., and Glenn in 1959, monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with a brass cap (properly) mkd.
 from which the remains of the bearing trees reported by Zirpel, Jr., and Glenn
 A decayed fir stump, 29" dia., bears N.57°W., 22.4 ft., with a healed blaze.
 and new bearing trees
 A fir, 9" dia., bears N.36½°E., 33.8 ft., mkd. ¼ S6 BT.
 A hemlock, 27" dia., bears S.35¼°E., 36.8 ft. mkd. ¼ S7 BT
 Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument unless a similar marker was already in place.

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 3/19/2024 - C.S. File 67/57-44

Found - BLM brass cap (properly mkd)
28" decayed Fir stump N.57°W., 22.4 ft.
9"x8' fir stump N.36½°E., 33.8 ft.
27" Hemlock S.35½°E., 36.6 ft. (rec. 36.8)

New - 42" burned Fir, S.40°W., 14.1 ft. 3½" mag nail right side center.

Note - Area burnt 9/2020
Compass decl. 14½°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone