

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4242)

Set granite stone, 5x8x14", 10" in the ground for the 1/4 sec. cor. marked 1/4 on W face; from which
 A fir, 10" dia., bears N.48°W., 21 lks., mkd: 1/4 S31 BT.
 A fir, 8" dia., bears N.80°E., 43 lks., mkd: 1/4 S32 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - D. West - July 1967 - C.S. File 54/40-20

Found - Orig. 10" now 15" Fir, alive, N.48°W., 13.9 ft. Open & find "BT" scribe & reverse, under 58 years ring count.
 Orig. 8" now 14" fir, down & rotting N.80°E., 28.4 ft., shows scar.
 5"x7"x13" stone mkd: "1/4" tipped out of position.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T26S R2W OFFICE 1967 1/4 S 31|S 32
Reset stone alongside
New BTs- 6" W.Fir S.69°W., 12.8 ft. mkd: 1/4 S31 CS BT
 9" D.Fir N.24°E., 19.4 ft. mkd: 1/4 S32 CS BT
Note - This corner on N-S cutting line cut off to East.

David Edwards - For: Seneca Jones Timber - 6/2010 - M 160-76

Found - DCSO Brass cap
 14" Dead Fir w/ HB brs. N.24°E., 19.4'.
New BTs- 7" dia., Fir brs. N.1°E., 12.65 ft.
 8" dia., Fir brs. S.54°W., 9.10 ft.
 4" dia., Fir brs. N.73°W., 4.60 ft.
 A 6 ft. steel post is set 2' north.