

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4245)

Set a granite stone 6x11x14", 10" in the ground for cor. for cor. of secs. 19, 20, 29, & 30 marked with 5 notch on E & 2 notches on S edge, from which

- A laurel, 4" dia., bears N.73°E., 38 lks., mkd: T26S R2W S20 BT.
- A laurel, 4" dia., bears S.63°E., 60 lks., mkd: T26S R2W S29 BT.
- A maple, 4" dia., bears S.13°W., 52 lks., mkd: T26S R2W S30 BT.
- A laurel, 4" dia., bears N.6°W., 43 lks., mkd: T26S R2W S19 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4332)

The cor. of secs. 19, 20, 29, & 30 established by Deputy Gibb in 1909, which is a granite stone, firmly set, marked & witnessed as described by the surveyor general.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - July 1967 - C.S. File 54/40-17

Found - Orig. 6"x11"x14" corner stone mkd. with 5 notches on E & 2 notches on S edges.
 Orig. 4" now 17" Laurel, S.63°E., 39.6 ft. alive. We open, center rotted, no scribe.
 Orig. 4" now 15" Maple S.18°W., 34.3 ft. Alive, showed scar, we open, center rotted, no scribe, bearing S.B. S.13°W.
 Orig. 4" now 16" Laurel, N.6°W., 28.4 ft. Alive, we open, center rotted, no scribe.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T26S R2W
 (in place of OFFICE S 19 | S 20
 corner stone) 1967 S 30 | S 29

New BTs- 9" Laurel S.12°E., 28.0 ft. mkd: T26S R2W S29 CS BT
 8" Chinquapin S.52°W. 13.9 ft mkd: T26S R2W S30 CSBT
 9" Chinquapin N.49°W. 34.3 ft mkd: T26S R2W S19 CSBT
 16" Pine N.76°E., 31.4 ft. mkd: T26S R2W S20 CS BT

Note - This corner lies on moderate SE slope.

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause - 11/15/2007 - C.S. File 67/24-50

Found - BC/IP not found continued next page

Alias	Description

Orig. 4" now 16" dia. Madrone, mostly dead, face has been chopped out & not healed, bears N.6°W., 28.4 ft. Agrees w/rec. OBT.

9" now 12" dia., chinquapin, healed lower blaze, open upper blaze with illegible scribe, bears N.49°W., 34.3 ft. agrees w/rec. 1967 BT.

16" now 40" dia., pine, healed double blaze, bears N.76°E., 31.4 ft. agrees w/rec. 1967 BT

No other accessories found.

Set - Position for brass cap determined by using record information. Set 2 3/8" dia., brass cap on 1 1/4" O.D. x 32" long iron pipe, projects 4" above ground. Brass cap mkd: COUNTY SURVEYORS OFFICE

T26S R2W
S 19 | S 20
S 30 | S 29
2007

22" dia., W.Pine, double blazed & scribed "T26S R2W S29 CS BT" bears S.56°E., 27.7 ft.

7" dia., D.Fir double blazed & scribed "X" on high blaze & "CS BT" on low blaze bears S.32°W. 23.0 ft

Fd. as per M155-46, by D. Edwards - C.S. File 65/74-1

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22935)

The cor. of secs. 19, 20, 29, and 30, perpetuated by the Douglas County Surveyor's Office in 1967 and 2007, monumented with an iron post, 1 1/4" dia, firmly set, projecting 5" above ground, with brass cap (properly) mkd. from which an original BT

A madrone, 16" dia, bears N.8 1/4°W., 28.4 ft., with axe marks visible on a previously chopped open and partially healed blaze. (Record, N.6°W.)

and BTs mkd. the Douglas County Surveyor's Office in 1967

A sugar pine, 45" dia, bears N.75 1/4°E., 32.1 ft., with a healed double blaze.

A chinquapin, 13" dia, bears N.49 1/4°W., 34.0 ft., with fragmentary scribe marks visible on partially healed blaze.

and BTs mkd. by the Douglas County Surveyor's Office in 2007

A sugar pine, 25" dia, bears N.56 1/4°E., 28.1 ft., with scribe marks 26R 2W S on upper and other fragmentary scribe marks visible on lower partially healed double blaze.

A fir, 8" dia, bears S.32°W., 23.1 ft., with scribe marks X on upper and BT visible on lower partially healed blaze.