

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4217-8)

Set a post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd ¼ S BT, from which
 A hemlock, 10" dia., bears N.40°W., 60 lks., mkd: ¼ S BT.
 A chinquapin, 6" dia., bears S.55°E., 35 lks., mkd: ¼ S BT

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12746)

Point for the ¼ sec. cor. of secs. 17 & 18, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2" dia., 25" in the ground and in a mound of stone, 2 ft. base, to top, with brass cap marked:
 T26S R2W
 ¼
 S 18|S 17
 1959
from which
 A hemlock, 20" dia. bears N.69¼°E., 18¾ lks. mkd: ¼ S17 BT
 A fir, 7" dia., bears N.49½°W., 38 lks., mkd: ¼ S18 BT.

Weyerhaeuser corner report by Glen McChesney stamped by Frank O. Williams - 3/11/1975 - C.S. File 59/11-13

Found - 1959 GLO brass cap
 20" hemlock, face healed over, BLM tag, bears N.69°E., 11.6 ft. to center of tree.
 8" fir leans to West, face healed over, BLM tag, bears N.49°W., 25.1 ft. to center of tree.
New - 16" hemlock bears S.7°W., 10.2 ft., with "W" nail & brass disc.
 20" sugar pine bears S.62°W., 15.0 ft., with "W" nail & brass disc.