

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4218)

Set a post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 7, 8, 17, & 18, marked T26S S8 on NE, R2W S17 on SE, S18 on SW, S7 on NW faces, with 4 notch on S & 5 notches on E edges; from which

- A fir, 10" dia. bears N.31°E., 22 lks. mkd: T26S R2W S8 BT
- A fir, 6" dia. bears S.16°E., 93 lks. mkd: T26S R2W S17 BT
- A fir, 14" dia. bears S.21°W. 33 lks. mkd: T26S R2W S18 BT
- A fir, 18" dia. bears N.38°W., 40 lks. mkd: T26S R2W S7 BT

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12746)

Point for the cor. of secs. 7, 8, 17, & 18, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground, at base of E side of a madrone, 15", with brass cap marked:

T26S	R2W
S 7	S 8
S 18	S 17
1959	

from which

- A hemlock, 12" dia., bears N.51°E., 66 lks., mkd: T26S R2W S8 BT.
- A cedar, 12" dia., bears S.54°E., 62 lks., mkd: T26S R2W S17 BT.
- A hemlock, 8" dia., bears S.75°W., 43 lks., mkd: T26S R2W S18 BT.
- A hemlock, 8" dia., bears N.33°W., 55 lks., mkd: T26S R2W S7 BT.

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 5/17/2005 - C.S. File 67/10-25

Found - 3" BC on 2½" IP projects 5" above ground US BLM cap dated 1959 (properly mkd)

- 12" now 15" hemlock, partially healed single blaze with illegible scribing visible bears N.48°E., 42.6 ft. (rec. N.51°E., 43.6 ft.)
- 12" now 18" R.Cedar partially healed single blaze with scribing "S2W S17 BT" visible bears S.54°E., 40.4 ft. (rec. S.54°E., 40.9 ft.)

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

8" now 12" Hemlock, now tipped onto rotted face no scribing visible, tree is still alive, bears N.33°W., 36.3 ft. to root hole.
SW BT gone.

New - 13" Chinquapin double blazed & scribed "T26S R2W S8 CS BT" bears N.89°E., 23.3 ft.
23" Madrone, bark scribed "T26S R2W S7 CS BT" N.78°W. 1.5 ft

Note - Corner is at base of 23" dia., Madrone on bench area of NE facing slope.

BLM dependent resurvey by Joel R Herzberg, Cadastral Surveyor under Group No. 2817, surveyed Oct./Nov. 2015 - (DCSO records Vol. 58 Page(s) 23487 & Plat T26-2 2017-1)

The cor. of secs. 7, 8, 17, & 18, perpetuated by the Douglas County Surveyor's Office in 2005, monumented with an iron post, 2½" dia., firmly set, projecting 4" above the ground, with brass cap (properly) mkd.
from which the remains of the BTs mkd. by Zirpel & Glenn in 1959
A root hole, bears N.45¾°E., 43.6 ft., with a fallen, decayed hemlock snag, 12" dia., lying alongside, with illegible scribe marks visible on a partially healed blaze. (Record, N.51°E.)
A cedar, 19" dia., bears S.54°E., 40.9 ft., with illegible scribe marks visible on a partially healed blaze.
and BTs mkd. by the Douglas County Surveyor's Office
A chinquapin, 14" dia., bears N.88°E., 23.3 ft., with scribe marks T26S R2W S8 CS BT visible on a partially healed blaze.
A madrone, 25" dia., bears N.58½°W., 1.8 ft., with scribe marks T26S R2W S7 CS BT visible on a partially healed bark scribe. Note: Base of tree is growing around the iron post.
and a new bearing tree
A hemlock, 15" dia., bears S.55°W., 36.0 ft., mkd. T26S R2W S18 BT.
Drive an aluminum angle iron, 5 ft. long, alongside the cor.