

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4220)

-----

Set a post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 5, 6, 7, & 8, marked T26S S5 on NE, R2W S8 on SE, S7 on SW, S6 on NW faces, with 5 notches on S & E edges; from which

A laurel, 10" dia., bears N.45°E., 24 lks., mkd: T26S R2W S5 BT.

A laurel, 18" dia., bears S.50°E., 47 lks., mkd: T26S R2W S8 BT.

A fir, 24" dia. bears S.55°W., 32 lks. mkd: T26S R2W S7 BT

A fir, 30" dia. bears N.15°W., 58 lks. mkd: T26S R2W S6 BT

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12749-5)

-----

The cor. of secs. 5, 6, 7, and 8, determined at record distance from each of the original bearing trees:

A madrone, 13" dia., bears N.51½°E., 24 lks., with a burned and rotted center. (Record bearing, N.45°E.)

A down and rotted madrone, 20" dia., bears S.50°E., 47 lks. dia., with no marks remaining.

A fir, 37" dia., bears S.61°W., 32 lks., with illegible bark scribes. (Record bearing, S.55°W.)

A fir, 45" dia., bears N.12½°W., 58 lks., with an opened and burned blaze. (Record bearing, N.15°W.)

At the corner point

Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap marked:

|      |     |   |   |
|------|-----|---|---|
| T26S | R2W |   |   |
| S    | 6   | S | 5 |
| S    | 7   | S | 8 |
| 1959 |     |   |   |

from which

A fir, 13" dia. bears N.25°E. 130 lks. mkd: T26S R2W S5 BT

A fir, 19" dia. bears S.71½°E. 90 lks. mkd: T26S R2W S8 BT

A fir, 20" dia. bears S.40½°W. 87 lks. mkd: T26S R2W S7 BT

A fir, 38" dia. bears N.21½°W. 55½ lks mkd: T26S R2W S6 BT

Glen McChesney - For: Weyerhaeuser Co. - April 1977 (Filed 12/1980) C.S. File 58/8-48

-----

Found - 1959 GLO brass cap, in place.  
 Down or broken remains of Madrone, N.51½°E., 15.8 ft. to root hole. (not fd. by Weyerhaeuser Co. records 7/7/67) (Orig. record 13", N.51½°E., 24 lks. 1959) 1883 Rec. N.45°E.) continued next page

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Evidence of old Madrone scattered by logging at approx. location of orig. 20" Madrone, down and rotted S.50°E., 47 lks.  
Down 38" Fir (W. Co. 7/7/67 record identified this BT S.60½°W., 21.6 ft.  
50" Fir (W. Co. 1967 record identified this BT, N.12°W., 38.1 ft.  
Down 16" Fir, face partly healed, BT tag. (1967 record identified this BT, N.25°E., 85.7 ft.)  
28" Fir stump, face and plates intact. (1967 record identified this BT, S.71°E., 59.6 ft.)  
22" Fir, down healed face and plate intact. (1967 record identified this BT S.40°W., 58.0 ft.)  
48" Fir, face and plate intact, (1967 record identified this BT N.22°W., 36.6 ft.)  
Accessories added this date:  
W nails and plates on:  
40" Fir stump, N.56°E., 59.2 ft.  
54" Fir stump, N.64°E., 65.2 ft.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2923, surveyed July 2018/March 2020- (DCSO records Vol. 59 Pages 24062-3)  
-----  
The cor. of secs. 5, 6, 7, and 8, reported by Zirpel, Jr., and Glenn in 1959; perpetuated by Williams, in 1977; monumented with an iron post, 2½" dia., firmly set, projecting 10" above ground, with a brass cap (properly) mkd. from which the remains of the bearing trees reported by Zirpel, Jr., and Glenn  
A decayed fir stump, size indeterminate, bears N.25°E., 85.8 ft., with a healed blaze.  
A decayed fir stump, 13" dia., bears S.71½°E., 59.4 ft., with scribe marks T26S R2W S8 BT visible on open blaze.  
A decayed fir stump, 23" dia., bears S.40½°W., 57.4 ft., no marks visible.  
A decayed fir stump, 36" dia., bears N.21½°W., 36.6 ft., with a healed blaze.  
A decayed fir stump, 39" dia., bears N.12½°W., 38.3 ft., with illegible scribe marks visible on open blaze.  
(Original)  
and the remains of the bearing trees mkd. by Williams  
A decayed fir stump, 45" dia., bears N.55¼°E., 60.1 ft., no marks visible.  
A decayed fir stump, 48" dia., bears N.63½°E., 66.8 ft., no marks visible.  
and new bearing trees  
continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A fir, 10" dia. bears N.69°E., 19.7 ft. mkd T26S R2W S5 BT  
A fir, 13" dia., bears S.67¼°E., 34.8 ft., mkd. T26S R2W S8 BT.  
A fir, 14" dia., bears S.11¼°W., 24.8 ft., mkd. T26S R2W S7 BT.  
A fir, 13" dia., bears N.11½°W., 14.8 ft., mkd. T26S R2W S6 BT.  
NAD 1983 (2011)  
Latitude: 43°19'37.77" N. Longitude: 122°58'13.97" W.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 8/22/2023 - C.S. File 67/56-59  
-----  
Found - 3¼" BLM brass cap (properly mkd) up 14"  
Burned broken off 13" decayed Fir stump S.71½°E., 59.4 ft.  
Burned decayed 36"x5 ft Fir stump N.21½°W., 36.6 ft.  
Burned decayed 39"x5 ft Fir stump N.12½°W., 38.3 ft.  
Burned decayed 43" Fir stump N.55¼°E., 60.1 ft.  
Burned decayed 46" Fir stump N.63½°E., 66.8 ft.  
Burned dead 10" fir N.69°E., 19.7 ft. open burned face.  
Burned sawn 20"x4" Fir stump S.67¼°E., 34.8 ft.  
Burned sawn 19"x5" Fir stump N.11½°W., 14.8 ft.  
New - Burned-dead 8" D.Fir N.36°E., 4.9 ft. 3½" mag nail, right side center.  
Burned-dead 7" D.Fir N.83°E., 15.9 ft. 3½" mag nail, right side center.  
Burned-dead 12" D.Fir S.1°E., 4.4 ft. 3½" mag nail, right side center.  
Burned-dead 35" Hemlock S.87°W., 32.0 ft. 3½" mag nail, right side center.  
Note - Area burnt 9/2020  
Mon. on moderate SW slope. NE & SW quads large reprod. NW & SE quads clear cut.  
Compass decl. 14½°E.  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 180204.055 E 260581.289