

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4223)

-----

Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on W face, from which:

    A fir, 12" dia., bears N.10°E., 26 lks., mkd: ¼ S BT.

    A fir, 12" dia., bears S.31°W., 14 lks., mkd: ¼ S BT.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12752)

-----

N.2°29'W. between secs. 5 & 6 - 46.135 chs.

Point for the ¼ sec. cor. of secs. 5 & 6, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 22" in the ground, an din a mound of stone, 3½ ft. base, to top, with brass cap marked:

T26S R2W  
          ¼  
          S 6 | S 5  
          1959

from which

    A cedar, 20" dia., bears S.41°E., 16 lks., mkd: ¼ S5 BT.

    A fir, 48" dia., bears N.60°W., 27 lks., mkd: ¼ S6 BT.

50.14 chs.

From this point a point determined at the intersection of the bearings from the faces of four BTs, of which I have no record, bears East, 1 lks. dist., from which

    A hemlock, 12" dia., bears N.42°E., 13½ lks., with scribe marks R2W S32 visible on a partially opened blaze. By counting annual growth rings, the age of the scribe marks were determined to be about 70 years old.

    A hemlock, 20" dia., bears S.46°E. , 30½ lks. with scribe marks R2W S5 visible on a partially opened blaze. By counting the annual growth rings, the age of the scribe marks were determined to be about 70 years old.

    A fir, 72" dia., bears S.51°W., 11 lks., with illegible scribe marks visible on a partially opened blaze. By counting the annual growth rings, the age of the scribe marks were determined to be about 55 years old.

    A fir, 30" dia., bears N.46°W., 38 lks., with scribe marks R2W S31 visible on a partially opened blaze. By counting the annual, growth. rings, the age of the scribe marks were determined to be about 55 years old.

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Frank O. Williams - For: Weyerhaeuser Co. - May 6, 1975 - C.S. File 59/8-19

-----  
Vicinity of 1/4 Cor. Secs. 5 & 6

Found - 12" Hemlock, scribing visible, N.42°E., 8.9 ft.  
20" Swell butt Hemlock, scribing visible S.46°E., 20.1 ft.  
72" Fir, scribing visible, put Weyerhaeuser plate at base of tree, tree to be felled. S.51°W., 7.3 ft.  
30" Fir, N.46°W., 25.1 ft. Tree felled, Weyerhaeuser plate at base of stump.

Weyerhaeuser plates are marked with 1959 GLO distances & reciprocal bearings.

NOTE - The GLO 1/4 cor. for secs. 5 & 6, a 1959 GLO brass cap with 2 BTs is South 4.00 chs.

Douglas Co. Surveyors Office - Gary L. Langlitz - A. Vic Cangie - 4/19/1976 - C.S. File 59/8-19

-----  
(This report is attached to the 1975 Weyerhaeuser report) Information of Unknown origin.

We find the trees mentioned in the attached Weyerhaeuser notes.

This information is also recorded in the 1959 Government resurvey notes on the section line between sections 5 & 6. There is no monument at this corner and no record of these apparent bearing trees.

We do not monument this corner.

Douglas Co. Surveyors Office - Gregory E. Quibell, Deputy - Teresa Buley, witness - Dec. 9, 1981 - C.S. 61/29-42

-----  
(Reference notes C.S. 59/30 now attached to this renewal.)

Found - 1959 BLM B.C., firmly set in mound of rocks, (Ref. notes) properly marked. Also, see 1975 Ren.

BTs - 48" Fir w/w nail per Ref. notes, bears N.61°W., 14.6 ft. to nail. Tree alive & well, shows good scar.

22" Cedar stump w/scribed "¼ S5 BT" visible as per Ref. notes, bears S.41°E., 10.6 ft.

60" Fir w/w nail per Ref. notes, bears N.65°E., 34.2 ft. to nail. Tree alive & well.

New BTs- 14" Hemlock scribed "¼ S6 CS BT" in dbl. blaze bears N.5°W., 14.7'.

12" Hemlock scribed "¼ S5 CS BT" in dbl. blaze bears S.26½°E., 25.1 ft.

Note - See C.S. 61/29 for sketch & Ref. notes.

cont.

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 8/15/2023 - C.S. File 67/56-55

-----  
Found - 3½" BLM brass cap (properly mkd) in rough stone mound, up 11"  
48"x2 ft burnt-sawn Fir stump N.64½°W., 17.5 ft. (Rec. N.61°W., 14.6 ft) add 3½" mag nail top center.  
62"x20 ft. burned broken off fir snag N.64°E., 36.3 ft. (rec. N.65°E., 34.2 ft.)  
14" Hemlock N.5°W., 14.7 ft. fully healed double blaze 3½" mag nail, right side center.  
11"x14 ft. broken burnt Hemlock snag S.26½°E., 25.1 ft.

New - 6"x2 ft. sawn burned Fir stump S.20°W., 39.5 ft. 3½" mag nail top center.

Note - Area burnt 9/2020  
Mon. 90'± East from gravel spur road.  
Mon. on nearly flat ground on N-S cut line, old growth east clear cut west.  
Compass decl. 14½°E.

Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 183247.027 E 206427.614