

PRIMARY CORNER DESCRIPTION CC Secs. 19 & 20 only, North

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4216)

-----

Set post, 4 ft. long, 4" sq., 24" in the ground for cor. of secs. 17, 18, 19, & 20, mkd T26S S17 on NE, R8W S20 on SE, S19 on SW & S18 on NW faces with 3 notches on S and 5 notches on East edges, from which

- A cedar, 36" dia., bears N.30°E., 64 lks., mkd: T26S R2W S17 BT.
- A hemlock, 10" dia., bears S.80°E., 55 lks., mkd: T26S R2W S20 BT.
- A fir, 36" dia., bears S.75°W., 16 lks., mkd: T26S R2W S19 BT.
- A cedar, 48" dia., bears N.50°W., 15 lks., mkd: T26S R2W S18 BT.

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4230)

-----

The cor. secs. 17, 18, 19, & 20, which is a stake greatly decayed, marked & witnessed as described by the Surveyor General.

Set granite stone, 8x10x14", 10" in the ground for cor. secs. 18, 17, 19, & 20, marked with 4 notches on E & 3 notches on S edge.

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol 10 Pages 4249-50)

-----

Set granite stone, 7x11x15", 10" in the ground for closing cor. secs. 19 & 20, marked C C on South, with 5 grooves on East & 1 groove on West face, from which

- A laurel, 8" dia., bears S.8°E., 52 lks., mkd: T26S R2W S20 BT.
- A maple, 7" dia., bears S.53°W., 35 lks., mkd: T26S R2W S19 BT.

I destroy markings on other cor. referring to secs. 19 & 20

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4333-4)

-----

**52.32 chs** The closing cor. of secs. 19 & 20, established by me in 1916, which is an iron post, 3 ft. long, 2" dia., 12" above ground, marked & witnessed as described by the surveyor genera. I now destroy this cor.

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 204400

PRIMARY CORNER DESCRIPTION CC Secs. 19 & 20 only, North

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

**67.28 chs** Intersect new S bdy. of sec. 17, 4.05 chs. N.87°04'E., of cor. of secs. 17 & 18.

At the point of intersection

Set an iron post, 3 ft long, 2" dia., 24" in the ground, for closing cor. of secs. 19 & 20, with brass cap marked

T26S R2W

S 17

S 19 | S 20

CC

1918

from which

A cedar, 12" dia., bears S.18°E., 37 lks., mkd: C C T26S R2W S20 BT.

A fir, 20" dia., bears S.59°W., 19 lks., mkd: C C T26S R2W S19 BT.

Cor. established by Gibb as closing cor. of secs. 19 & 20 bears S.0°23'W., 14.79 chs.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12745)

-----  
The closing cor., of secs. 19 & 20, monumented by Mensch in 1918, with an iron post, 2" dia., protruding 8" above ground, firmly set, with brass cap (properly) mkd., from which

A cedar, 14" dia., bears S.18°E., 37 lks. with scribe marks 2 20 B visible on a partially open blaze.

A fir, 28" dia., bears S.59°W., 19 lks. with a healed blaze.