

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 32; & S 5, T27-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by S.C. Flint, Contract #459, dated August 3, 1882  
- (DCSO records Vol. 10 Page(s) 4181-82)  
-----  
Set Cedar post 3 ft. long, 3' sq., 24" in the ground for ¼  
sec. cor. marked ¼ S. on N. & S. face, from which  
    A Laurel 20" dia., bears N.35°W., 7 lks. dist. mkd. ¼ S BT  
    A Fir 20" dia., bears S.35°E., 30 lks. dist. mkd. ¼ S BT.

Fd. and tied corner in GLO survey by C.M. Collier, Deputy  
Surveyor, under Instructions dated May/Sept. 1913 - (DCSO  
records Vol. 10 Page(s) 4259)

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
July 1967 - C.S. File 54/40-33  
-----  
Found - Orig. 20" now 22" Laurel, N.35°W., 4.6 ft., alive,  
        scribe visible on unhealed blaze.  
        Orig. 20" now 32" Fir, S.35°E., 19.8 ft., alive,  
        bark scribe "¼ B" in fair condition.  
Set Brass cap at cor. mkd:           County Surveyors Office  
  ¼  $\frac{S\ 32}{S\ 5}$            T26S   R2W  
  T27S  
  1967

New BTs- 12" D.Fir N.8°W., 12.8 ft. mkd. ¼ S32 CS BT.  
          20" W.Fir S.1°W., 9.0 ft. mkd. ¼ S5 CS BT.  
Corner lies on top of ridge, sloping South and E-W cutting  
line, cut off to North.

Fd. DCSO cap & 4 BTs - By D. Edwards, 6/2010 - M160-76

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff  
Lorsung- 4/1/2024 - C.S. File 67/57-47  
-----  
Found - 2½" DCSO brass cap (properly mkd) up 15"  
        Shattered broken 6½ ft. Madrone N.35°W., 4.6 ft.  
        34" D.Fir S.35°E., 20.1 ft. (rec. 19.8 ft) visible  
        blaze add 3½" mag nail right side center.  
        Sawn 20"x8 ft. D.Fir stump N.8°W., 12.8 ft, fully  
        healed double blaze, add 3½" mag nail right side  
        center.  
        31" W.Fir S.1°W., 9.0 ft. fully healed double blaze,  
        add 3½" mag nail right side center.  
        Metal post 2.0 ft west.  
New - 21"x 1½ ft. D.Fir stump N.54°W., 18.4 ft. 3½" mag  
      nail top center.  
Note - Forested to south, young reprod to North.  
      Area burnt 9/2020  
continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 32; & S 5, T27-2

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Compass decl. 14½°E.  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 154703.925      E 263191.959