

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

<p>GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4246) ----- Set cedar stake, 3 ft. long, 4" sq. 24" in the ground for 1/4 sec. cor. mkd: 1/4 S20 on N & 29 on S face, from which A cedar, 10" dia., bears N.21°E., 24 lks., mkd: 1/4 S20 BT. A fir, 8" dia., bears S.38°E., 12 lks., mkd: 1/4 S29 BT.</p>
<p>GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4334) ----- Intersect the 1/4 sec. cor. established by Deputy Gibb in 1909, which is a cedar post, 4" sq. 12" above ground, firmly set, marked & witnessed as described by the surveyor general</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - March 1967 - C.S. File 54/40-13 ----- Found - Unrecorded 3/4" I.Rod which bears S.4 1/2°E., 9.6 ft. from true corner. Orig. 10" now 22" Cedar, down & burned, N.21°E., 15.8 ft., no scribe found. Orig. 8", now 16" Fir snag, S.38°E., 7.9 ft., open & find "1/4S" scribe. Set - Brass cap at cor. mkd: County Surveyors T26S R2W Office 1/4 S 20 S 29 New BTs- 9" D.Fir N.56°W., 47.8 ft. mkd: 1/4 S20 CS BT. 15" Cedar S.33°W., 94.9 ft. mkd: 1/4 S29 CS BT. Note - This area logged off & grown up to dense greasewood brush. Corner on gentle SE slope approx. 200 ft. E of logging road.</p>
<p>Fd. BC & 2 BTs by D. Edwards, 4/2008 - M155-46</p>
<p>Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 6/1/2023 - C.S. File 67/56-29 ----- Found - 2 1/2" DCSO brass cap (properly mkd) up 14" Burned-dead, 23" D.Fir N.56°W., 47.8 ft. healed single blaze add 3 1/2" mag nail right side center. Mostly burned away 3 ft. cedar stump S.33°W., 92.9 ft. (rec. 94.9 ft) Galvanized steel post 2 ft north. New - Burned, dead 14" D.Fir N.82°E., 10.8 ft. 3 1/2" mag nail right side center not blazed or scribed. Continued next page</p>

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Burned, sawn 20"x1½ ft. D.Fir stump S.55½°W., 14.0
ft. 3½" mag nail top center.
Note - Area burnt 9/2020
Compass decl. 14½°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
~~196994.917 N~~ ~~262899.879 E~~ corrected 8/21/2024
N 165107.084 E 263207.341