

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 240440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12757)

Point for the center Sec. cor. of sec. 17, at intersection with the E & W center line.

Set an iron post, 28" long, 2½" dia., 25" in the ground, with brass cap mkd. C ¼ S 17

1959

from which

A hemlock, 18" dia., bears N.75½° E. , 72½ lks., mkd. C ¼ S17 BT.

A hemlock, 8" dia. bears S.24½°W., 42 lks. mkd. C ¼ S17 BT

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - Oct. 24, 1994 - C.S. File 64/52-10

Found - 3¼" dia. brass cap on a 2½" O.D. iron pipe, protrudes 2" above ground. (1959 BLM)

18" now 21" dia. Hemlock with a fully healed single blaze, bears N.75¼°E., 47.8 ft. (1959 BLM)

8" now 14" dia. Hemlock with a fully healed single blaze bears S.24½°W., 27.2 ft. (rec. S.24½°W., 27.7 ft. is a slope measurement) (1959 BLM)

New - 10" Maple, double blazed and scribed "C¼ S17 CS BT" bears N.1°W., 27.2 ft.

7" Maple, double blazed and scribed "C¼ S17 CS BT" bears N.89°W., 5.2 ft.

Note - Corner lies in old growth timber on a bench.