

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under contract No. 466, dated April 5, 1883 - (DCSO records Vol. 10 Page(s) 4219)

Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on N face, from which:
A maple, 4" dia., bears N.10°E., 9 lks., mkd: ¼ S BT.
A maple, 6" dia., bears S.65°E., 32 lks., mkd: ¼ S BT.

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12747)

Point for ¼ sec. cor. of secs. 8 & 17, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
T26S R2W
¼ S 8
 S 17
 1959

from which
A fir, 20" dia., bears N.53½°W., 17 lks., mkd: ¼ S8 BT.
A fir, 15" dia., bears S.41°E., 34 lks., mkd: ¼ S17 BT.

Ken Hoffine - For: Lone Rock Management Co. - 5/2016 - M172-7

Found - 1959 BLM brass cap 0.4 feet above ground.
20" D.Fir bears S.41¼°E., 22.11 ft (record S.41°E., 22.44 ft) healed face and BLM tag.
28" D.Fir bears N.57°W., 10.3 ft (record N.53½°W., 11.22 ft) healed face and BLM tag.
Corner lies on steep south facing slope approx. 100 ft south of old roadway.