

PRIMARY CORNER DESCRIPTION Center East 1/16 Sec 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Irving Zirpel, Jr. & Wm. Glenn, Cadastral Surveyors, Group No. 404, surveyed May/Oct. 1959 - (DCSO Vol. 30 Page(s) 12758)

-----  
Point for the center E 1/16 sec. cor, of sec. 17.  
Set an iron post. 28" long, 2½" dia., 24" in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

C  $\frac{E \ 1/16}{S \ 17}$  C  
1959

from which

A fir, 11" dia., bears N.80½°W., 36 lks., mkd. C E 1/16 S17 BT.

A fir, 11" dia., bears S.2¼° E., 20 lks., mid. C E 1/16 S17 BT.

From this point the NE. cor, of a wood frame lean-to, bears N.75°46'E., 510 lks., dimensions 18 x 12 ft., longside bears S.45°W.

From the same point the SE. cor, of a wood frame dwelling, an old logging camp building, unoccupied, bears N.80°14'E., 561 lks., dimensions 50½ x 20 ft., longside bears N.50°E.

From the same point the NE. cor. of a wood frame building, bears N.86°02'E., 505 lks., dimensions 64½ x 23 ft., longside bears S.50°E. Cor. falls at foot of descent, slopes N.; asc. 8 ft. over NE. slope.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - June 8, 1992 - C.S. File 64/26-14

-----  
Found - 3" BLM brass cap on a 2½" O.D. iron pipe protruding 2" above a 2 ft. dia. mound of stone. Cap is marked: "U.S. Cadastral Survey C E 1/16 1959 Bureau of Land Management"

11" now 16" dia. D.Fir with a fully healed single blaze, bears N.80½°W., 22.9 ft. (rec. N.80½°W., 23.8 ft. to center of trunk 1959 survey)

11" now 17" dia. 3 ft. high D.Fir stump with a fully healed single blaze, bears S.2¼°E., 13.2 ft. (agrees with rec. 1959.survey)

New - 7" dia. D.Fir double blazed & scribed "CE 1/16 S17 CS BT" bears S.46°W., 7.4 ft.

13" dia. Maple, double blazed & scribed CE 1/16 S17 CS BT" bears N.44½°W., 18.5 ft to center of trunk

11" dia. I.Cedar, double blazed & scribed "CE 1/16 S17 CS BT" bears S.18½°E., 67.0 ft.

Note - Corner lies 5 ft. south of creek bank.

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 260440

PRIMARY CORNER DESCRIPTION Center East 1/16 Sec 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Crew: Stephen Flauser & Jeff Lorsche - 5/9/2022 (Filed 8/11/2022) - C.S. File 67/52-46

-----  
Found - 3/4" brass cap on 2/4" iron pipe n rough mound of stone proj. 4"  
10"x6' Fir snag N.80 1/2°W., 22.9 ft mostly burnt away.  
20" D.Fir S.46°W., 7.4 ft. healed double blaze. Tree singed by fire.  
15" Maple N.44 1/2°W., 18.5 ft. healed double blaze singed by fire.  
29" I.Cedar S.18 1/2°E., 67.0 ft. healed double blaze, slight burn bark at base.

Add 3 1/2" PKs to right side center of Fd BTs  
Note - Stream now 50'± north.  
Area burnt 9/2020  
Compass decl. 14 1/2°E.  
See sketch in file.

Lat: 43°18'21.17"N Long: 122°57'24.73"W