

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 273346

PRIMARY CORNER DESCRIPTION SW Cor. Tract 37 (Cor. #4)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4338)

Intersect McQuinn line & old S Bdy of Sec. 17 at temp. SW cor. of Tract 37
Set an iron post, 3 ft. long, 1" dia., 26" in the ground for cor. No. 4 of Tract 37, with brass cap marked:

T26S | TR 37
R2W | 4
S20
1918

from which
A fir, 40" dia., bears N.19°E., 54 lks., mkd: 4 TR 37 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Aug. 1967 - C.S. File 54/40-72

Found - Orig. 40" now 48" fir, alive, N.19°E., 35.6 ft., shows good scar. After much excavation in area of large turned-out fir, we find IP & brass cap, 1918, out of position in good condition.
Reset - Brass cap, properly mkd in 1918 in proper locus.
New BT - 5" W.Fir N.65°E., 18.5 ft. mkd: 4 TR 37 CS BT.
Note - Corner lies on steep east slope in heavy timber.

FD. Mensch BC, by G Lang, 11/2013 - C.S. file 65/79-17