

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 274700

PRIMARY CORNER DESCRIPTION C C for Secs. 32 & 33 only, T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO recs Vol. 9 Pg 3628)

-----  
At point of intersection (600 lks. W. of cor. of secs. 4, 5, 32 and 33), I SET a basalt stone 15x11x6 ins., 10" in the ground for closing cor. of secs. 32 and 33, mkd. C C with 4 notches on E. and 2 notches on W. edges, from which

A Hemlock 10" dia., bears N.20°E., 42 lks. dist. mkd. C C  
T25S R2W S33 BT.

A Hemlock 4" dia., bears N.51°W., 65 lks. dist. mkd. C C  
T25S R2W S32 BT.

GL0 survey by C.M. Collier, Deputy Surveyor, under Instructions dated May/Sept. 1913 - (DCSO rec Vol 10 Pg 4274)

-----  
Searched for closing cor. of secs. 32 and 33, but could find no trace of same.

BLM Resurvey by Irving Zirpel & Wm. Glenn Under Group #404, Surveyed May/Oct. 1959 - (DCSO records Vol. 30 Page(s) 12721)

-----  
Find no evidence of the closing cor of secs 32 & 33, T25S R2W

V. W. Hosford, Surveyor - For: Evans Products Company - Feb/Oct. 1960 - C.S. File 51/144

-----  
At 408.6 ft., S.89°45'W., from sec. cor. for 4 & 5, I established the C.C. of secs.32 and 33. At this point, I could find no evidence of the corner Johnson describes in his notes of 1900. At the true point of the closing corner, I drove a 1½" Iron pipe, 36" long, 12" above ground, from which  
10" Hemlock bears N.47½°E., 11.4 ft. mkd. T25S CC S33 253  
BT.

16" Hemlock bears N.14¼°W., 45.2 ft. mkd. R2W C.C. S32 253  
BT.

BLM Resurvey by Daniel Berry; Harvey Wofford; G. Steven Popken, Cadastral Surveyors, under Group #'s 786, 848 and 854. And Glenn S. Baughman, L.S. #536, under Contract #52500-CT5-1116, Surveyed July 1972/Oct. 1975 - (DCSO records Vol. 36 Page(s) 15104-05)

-----  
The closing cor. of 32 & 33, T25S R2W, reestablished at proportionate measurement by Hosford in 1960, monumented with an iron pipe, 1½" dia., firmly set, protruding 8" above ground, from which bearing trees mkd. by Hosford:

(Cont. Next Page)

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 274700

PRIMARY CORNER DESCRIPTION C C for Secs. 32 & 33 only, T25-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

an iron pipe, 1½" dia., firmly set, protruding 8" above ground, from which bearing trees mkd. by Hosford:

A root hole bears N.47°E., 18 lks. dist., with a down Hemlock alongside, 13" dia., with scribe marks T25S CC S33 253 BT visible on open blaze.

A Hemlock 16" dia., bears N.12°W., 69 lks. dist., with scribe marks R2W CC S32 253 BT visible on partially healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd:

C C  
T 25 S | R 2 W  
    S 32 | S 33  
    S 5  
T 26 S R 2 W  
1972

from which new bearing tree:

A Fir 8" dia., bears N.37°E., 45 lks. dist. mkd. T25S R2W S33 CC BT.

Deposit the iron pipe alongside the iron post.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2919, surveyed May 2018/July 2020 - (DCSO records Vol. 59 Page(s) 23914-5)

-----  
The closing cor. of secs. 32 & 33, on the S bdy of T25S R2W monumented with an iron post 2½" dia firmly set projecting 5" above ground, (alongside of which is an iron pipe, 2" dia., firmly set, projecting 5" above ground) in a collar of stone, with a brass cap (properly) mkd.

from which the remains of a BT mkd. by Hosford, in 1960, reported by Berry, Wofford, Popken, and Baughman in 1972-75

A roothole bears N.8½°W., 41.8 ft., alongside of which is an uprooted tin-capped, decayed hemlock stump, 16" dia. with no marks visible on open blaze. (Record, bears N.12°W., 45.5 ft.)

and the remains of a BT mkd. by Berry, Wofford, Popken, and Baughman in 1972-75

A roothole bears N.37°E., 29.7 ft., alongside of which is a down decayed fir, 16" dia., with illegible scribe marks visible on partially healed blaze

and new bearing trees

A fir, 9" dia., bears N.27¼°E., 14.2 ft., mkd. T25S R2W CC S33 BT

A fir, 8" dia., bears N.31¾°W., 19.1 ft., mkd. T25S R2W CC S32 BT

continued next page

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 274700

PRIMARY CORNER DESCRIPTION C C for Secs. 32 & 33 only, T25-2

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.