

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4239)  
-----  
Set a granite stone 8x8x12" 8" in the ground for ¼ sec. cor. marked ¼ on W face, from which  
    A hemlock, 10" dia., bears S.33°E., 20 lks., mkd: ¼ S28 BT  
    A cedar, 8" dia., bears N.45°W., 51 lks., mkd: ¼ S29 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Aug. 1967 - C.S. File 54/40-65  
-----  
Found - 8x10x12" stone, set in mound of stone, no marks found.  
    Orig. 10" now 26" hemlock, alive, S.33°E., 13.2 ft. prev. opened & shows "¼ S29 BT" scribe.  
    Also find pieces of overgrowth with reverse scribe. Orig. 8" now 13" cedar snag, N.40°W., 40.0 ft. (rec. N.45°W., 33.7) previously opened & shows "¼" Open lower & find "BT"  
  
Set - Brass cap at cor. mkd: County Surveyors T26S R2W Office 1967 ¼ S 29 S 28  
    (Set under 36" long lying across corner point)  
New BTs- 7" hemlock N.48°E., 22.0 ft. mkd: ¼ S28 CS BT.  
    9" hemlock S.70½°W., 20.1 ft. mkd: ¼ S29 CS BT.  
Note - This corner lies on flat bench area.

Gerald Nygren - For: Seneca Jones Tbr. Co. - April 23, 1999 (Rec'd & filed April 15, 2010) - C.S. File 65/70-3  
-----  
Fd. 1967 Co. Surveyor brass cap, from which bears:  
    (Orig.) 26" dia, Hemlock, S.33°E., 13.2 ft. (vis. scribe)  
    (1967) 11" dia., Hemlock, S.70°30'W., 20.1 ft. (healed face)  
    (1967) 9" dia., Hemlock, N.48°E., 22.0 ft. (vis. scribe)

FD. Ok by T. Hostetter, 12/2005 - M149-17

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2331, Surveyed April/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22932)  
-----  
The ¼ sec. cor. of secs. 28 and 29, perpetuated by the Douglas County Surveyor's Office in 1967, monumented with an iron post, 1¼" dia., firmly set, projecting 14" above a collar of stone, (lying out of the ground nearby is the original igneous stone (Record, granite) 8x8x12", with marks ¼ visible) with brass cap (properly) mkd. cont. next pg

TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees  
A hemlock, 27" dia., bears S.33°E., 13.2 ft., with scribe marks ¼ S28 BT visible on a previously chopped open and now partially healed blaze.  
A cedar snag, 12" dia., bears N.41½°W., 40.0 ft., with scribe marks ¼ and other fragmentary scribe marks visible on a chopped open blaze. (Record, N.45°W., 33.7 ft.)  
and the BTs mkd. by the Douglas County Surveyor's Office  
A hemlock, 9" dia., bears N.45¾°E., 22.1 ft., with a healed double blaze.  
A partially uprooted hemlock, 13" dia., bears S.68½°W., 20.3 ft., with a healed double blaze.  
and a new bearing tree  
A cedar, 22" dia., bears S.58¾°W., 44.9 ft., mkd. ¼ S29 BT.  
Incorporate original stone into collar of stone.  
Corner is located 250 ft. S. of a gravel road, 15 ft. wide, bears N.60°W. and S.65°E., in a curve.  
NAD 1983 (CORS 96)  
Latitude: 43°16'43.90"N Longitude: 122°57'03.08"W

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 11/3/2021 (Filed 11/23/2021) - C.S. File 67/51-25  
-----  
Found - 1967 DCS0 2½" DCS0 brass cap on 1" I.D. iron pipe projecting 11" (properly mkd)  
28" dead Hemlock S.33°E., 13.6 ft. (rec. 13.2) scribes visible on chopped open face. OBT  
Uprooted 13" Hemlock S.68½°W., 20.3 ft. (Root Hole) 1967 DCS0  
Dead burned 24" Cedar S.58¾°W., 45.2 ft (Rec. 44.9 ft) Healed blaze. 1967 DCS0  
Collar of stone scattered, original stone not found.  
New - Dead 11"x3½" ft Hemlock marked "L" "O" "A" in bark S.21°W., 13.0 ft.  
Note - Corner is 250 ft South of gravel road.  
Area burnt in Archie Fire 9/2020  
Compass decl. 14½°E.  
Latitude: 43°16'43.90"N Longitude: 122°57'03.08"W  
NAD 1983 (CORS 96)