TOWNSHIP 26 RANGE 02 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. N Gibb, Deputy Surveyor, under contract No. 783, dated Dec. 3, 1908 - (DCSO records Vol. 10 Page(s) 4239)

Set granite stone 8x8x12", 8" in the ground for cor. for cor. of secs. 20, 21, 28, & 29 marked with 4 notches on E & 2 notches on S edge, from which

A cedar, 6" dia., bears N.47°E., 18 lks., mkd: T26S R2W S21 BT.
A maple, 6" dia., bears S.43°E., 20 lks., mkd: T26S R2W S28 BT.
A hemlock, 16" dia., bears S.32°W., 16 lks., mkd: T26S R2W S29 BT.
An alder, 7" dia., bears N.45°W., 22 lks., mkd: T26S R2W S20 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated May 25, 1916 & April 16, 1918, - (DCSO records Vol. 10 Page(s) 4331)

The cor. of secs. 20, 21, 28, & 29, established by Deputy Gibb in 1909, which is a granite stone, firmly set, marked & witnessed as described by the surveyor general.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Aug. 1967 - C.S. File 54/40

Found - 8"x8"x14" corner stone mkd, with 2 notches on S & 4 notches on E.
Orig. 6" now 12" cedar, alive, N.47°E., 11.9 ft. shows scar. Rescribe: "T26S R2W S21 CS BT"
Orig. 6" now 11" Maple, alive, S.43°E., 13.2 ft. shows scar. Rescribed: "T26S R2W S28 CS BT"
Orig. 16" now 24" hemlock alive S.32°W., 10.6 ft., scribe marks visible on open blaze.
No trace of NW BT.

Set - Brass cap at cor. mkd: County Surveyors Office 1967

T26S R2W	
S 20	S 21
S 29	S 28

New BTs- 7" cedar S.87°W., 34.1 ft. mkd: T26S R2W S29 CS BT
14" yew N.26°W., 94.0 ft. mkd: T26S R2W S20 CS BT

Note - Corner lies on moderate NW slope on old N-S cutting line, cut off to west.

Fd. Ok by T. Hostetter, 12/2005 - M149-17
Fd. BC & 5 BTs by D. Edwards, 4/2008 - M155-46